



TIKKURILA
FEELINGS MOISTURE STOP



- DESCRIPTION** Moisture stop which forms an impervious surface
- RECOMMENDED USES** Particularly suitable for wet areas of kitchens, bathrooms, shower rooms, utility rooms, swimming pool areas etc.
- PRODUCT FEATURES** Suitable for plaster, building blocks and boards, etc. Can be used on surfaces previously coated with waterborne, alkyd or acid catalysed paints and glass-fibre wall coverings

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

FEELINGS MOISTURE STOP

TECHNICAL DATA

Colour Shades	Translucent
Coverage	4-6 m ² /l unthinned. The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.
Can sizes	3 l
Application method	Brush, roller or spray application. Thinning: when necessary, thin with water.
Drying time (23°C and 50% relative air humidity)	Normally touch-dry in 4 hours and recoatable with Feelings Extra Durable paint after approx. 4 hours.
Density (kg/l)	Approx. 1.2 kg/l, ISO 2811
Volume solids (%)	39
VOC	(cat A/i) 140g/l (2010)
Storage	Protect from frost



FEELINGS MOISTURE STOP

APPLICATION INSTRUCTIONS

Application conditions

All surfaces to be painted must be dry, the temperature of the air at least +10°C and the relative humidity of the air below 80%.

Surface preparation

Remove all dirt and dust. If surface to be treated has mould damages, find out the reason for them and repair them carefully before painting. Remove loose, flaking paint with a scraper. Remove vinyl wall coverings and ceramic tiles in full. Sand glossy paint surfaces to a matt finish. Wash the surface with Maalipesu (Cleaning Agent), if necessary and rinse carefully with water. Fill concrete, plaster etc. surfaces with Presto LV Humid Room Filler. Sand the surface and remove sanding dust.

Application

Stir Feelings Moisture Stop well before use. Apply two coats of moisture stop with a roller and finish off corners and inlets by brush. Allow to dry for 1-4 hours between treatments. Finish with Feelings Extra Durable after approx. 4 hours from the second treatment with moisture stop.

Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Environmental and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.