

## DECLARATION OF PERFORMANCE

### Finnseco Fibre Render

No. TIK-1630-5012

1. Unique identification code of the product type: **TIK-1630-5012 Finnseco Fibre Render**
2. Intended use: **General purpose rendering/plastering mortar (GP) & Adhesive, reinforcement and levelling mortar for indoor and outdoor use**
3. Manufacturer: **Tikkurila Oyj. P.O.Box 53, FI-01301 Vantaa**
4. System of AVCP: **AVCP 4**
5. Harmonised standard: **EN 998-1:2010**
6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Dry bulk density	NPD	EN 998-1:2010
Compressive strength	CS IV	
Adhesion	≥ 1.0 N/mm <sup>2</sup> concrete (fracture pattern B)	
Adhesion after weathering cycles	NPD	
Capillary water absorption	W 0	
Water penetration after capillary water absorption test	NPD	
Water permeability after weathering cycles	NPD	
Water vapour permeability coefficient, $\mu$	NPD	
Thermal conductivity mean $\lambda_{10,dry,mat}$ -values	NPD	
Reaction to fire	A 2	
Durability	NPD	
Release of dangerous substances	NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on the behalf of the manufacturer by:

Leif Wirtanen

At Vantaa on 12.2.2016

A handwritten signature in blue ink, appearing to read 'Leif Wirtanen', with a large circular flourish at the end.