

## DECLARATION OF PERFORMANCE

### Finnseco Thick Render Fine

No. TIK-7100-5001

1. Unique identification code of the product type: **TIK-7100-5001 Finnseco Thick Render Fine**
2. Intended use **General purpose rendering/plastering mortar (GP) & Reinforcement and levelling mortar for outdoor use**
3. Manufacturer: **Tikkurila Oyj. P.O.Box 53, FI-01301 Vantaa**
4. System of AVCP: **AVCP 4**
5. Harmonised standard: **EN 998-1:2010**
6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Dry bulk density	NPD	EN 998-1:2010
Compressive strength	CS III	
Adhesion	≥ 0.15 N/mm <sup>2</sup> concrete (fracture pattern B)	
Adhesion after weathering cycles	NPD	
Capillary water absorption	W 0	
Water penetration after capillary water absorption test	NPD	
Water permeability after weathering cycles	NPD	
Water vapour permeability coefficient, $\mu$	15/35	
Thermal conductivity mean $\lambda_{10,dry,mat}$ -values	≤ 0.67 W/mK (P=50%) ≤ 0.76 W/mK (P=90%) (tabulated value according to EN 1745)	
Reaction to fire	A 1	
Durability	NPD	
Release of dangerous substances	NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on the behalf of the manufacturer by:

Magnus Engblom

At Vantaa on 14.2.2017

A handwritten signature in blue ink, appearing to read 'Magnus Engblom', followed by a long horizontal flourish.