

## DECLARATION OF PERFORMANCE

Temafloor 500M epoxy coating

No TIK-A018-2018

1. Unique identification code of the product type: **TIK-A018-2018 Temafloor 500M**
2. Intended uses: **Product for protection and repair of concrete structures – Coating: ingress protection (1.3), physical resistance (5.1), chemical resistance (6.1)**
3. Manufacturer: **Tikkurila Oyj, Kuninkaalantie 1, FI-01300 Vantaa**
4. Systems of assessment and verification of consistency of performance of the construction product: **AVCP 2+ and AVCP 3**
5. Harmonised standard: **EN 1504-2:2004**

Notified body: **AVCP 2+: 0809 VTT Expert Services Oy**

**AVCP 3: 0809 VTT Expert Services Oy (VTT-S-3318-10)**

6. Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Linear shrinkage	NPD	EN 1504-2:2004
Compressive strength	NPD	
Coefficient of thermal expansion	NPD	
Abrasion resistance	weight loss < 3000 mg	
Adhesion by cross-cut test	NPD	
Permeability to CO <sub>2</sub>	CO <sub>2SD</sub> > 50 m	
Permeability to water vapour	class II, 5 m < s <sub>D</sub> < 50 m	
Capillary absorption and permeability to water	$w < 0.1 \text{ kg/m}^2 \cdot \text{h}^{0.5}$	
Adhesion after thermal compatibility	NPD	
Resistance to thermal shock	NPD	
Chemical resistance	NPD	
Resistance to severe chemical attack	class II	
Crack bridging ability	NPD	
Impact resistance	class I: $\geq 4 \text{ Nm}$	
Adhesion strength by pull-off test	$\geq 2.0 \text{ N/mm}^2$	
Fire classification	B <sub>fl</sub> -s1	
Slip/skid resistance	NPD	
Behaviour after artificial weathering	NPD	
Antistatic behaviour	NPD	
Adhesion on wet concrete	NPD	
Diffusion of chloride ions	NPD	
Release of dangerous substances	NPD	

Resistance to severe chemical attack:

- Group 1: Petrol
- Group 2: Aircraft fuel
- Group 1: Petrol
- Group 2: Aircraft fuel
- Group 3: Heating oil, diesel fuel, unused engine and lubricating oils
- Group 4: All hydrocarbons, excluding groups 4a and 4b
- Group 4a: Benzene and benzene containing solutions
- Group 4b: Crude oil
- Group 5: Aqueous solutions of alcohols (max. 48 vol.-% methanol) and glycol ethers
- Group 5a: All alcohols and glycol ethers
- Group 6: Halogenated hydrocarbons
- Group 6a: Halogenated aliphatic hydrocarbons
- Group 6b: Halogenated aromatic hydrocarbons
- Group 7: Organic esters and ketones
- Group 7a: Aromatic esters and ketones
- Group 8: Aliphatic aldehydes
- Group 9: Aqueous solutions of organic acids, up to 10%
- Group 9a: Organic acids (excluding formic acid) and aqueous solutions of their salts
- Group 10: Inorganic acids (up to 20 %) and aqueous solutions of acidic salts (pH < 6)
- Group 11: Inorganic bases and their alkaline hydrolyzing salts (pH > 8)
- Group 12: Inorganic non-oxidizing salts (pH 6-8)
- Group 13: Aqueous solutions of amines and their salts
- Group 14: Aqueous solutions of organic tensides
- Group 15: Cyclic and acyclic ethers
- Group 15a: Acyclic ethers

Detailed descriptions of chemical groups and test solutions can be found in standard EN 13529.

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on the behalf of the manufacturer by:

Magnus Engblom, RDI Manager

At Vantaa 15.10.2018

