DECLARATION OF PERFORMANCE

Temafloor Primer epoxy primer

No TIK-8400-5017

- Unique identification code of the product type: TIK-8400-5017 Temafloor Primer, as part of a system
- 2. Intended uses: Product for protection and repair of concrete structures Coating: ingress protection (1.3), physical resistance (5.1)
- 3. Manufacturer: Tikkurila Oyj, Kuninkaalantie 1, Fl-01300 Vantaa
- 4. System of assessment and verification of consistency of performance of the construction product: **AVCP 2+**
- 5. Harmonised standard: **EN 1504-2:2004**

Notified body: AVCP 2+: 0809 VTT Expert Services Oy

Declared performances:

Essential characteristics	Performance	Harmonised technical specification
Linear shrinkage	NPD	-
Compressive strength	NPD	
Coefficient of thermal expansion	NPD	
Abrasion resistance	according to the top coat	
Adhesion by cross-cut test	NPD	
Permeability to CO ₂	according to the top coat	
Permeability to water vapour	according to the top coat	
Capillary absorption and permeability to water	according to the top coat	
Adhesion after thermal compatibility	NPD	
Resistance to thermal shock	NPD	
Chemical resistance	NPD	EN 1504-2:2004
Crack bridging ability	NPD	
Impact resistance	according to the top coat	
Adhesion strength by pull-off test	≥ 2.0 N/mm ²	
Fire classification	E _{fl} (NPD)	
Slip/skid resistance	NPD	1
Behaviour after artificial weathering	NPD	
Antistatic behaviour	NPD	
Adhesion on wet concrete	NPD	
Diffusion of chloride ions	NPD	
Release of dangerous substances	NPD	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on the behalf of the manufacturer by:

Merja Koivisto

At Vantaa on 21.9.2016

they a Krivisto