



TIKKURILA

ETERNIT PRIMER

DESCRIPTION

Primer for fibre cement roofs.

RECOMMENDED USES

Eternit Primer is used on fibre cement, fibre cement slates and concrete.

Eternit Primer is not suitable for use on clay tiles or natural slate.

PRODUCT FEATURES

Eternit Primer is a waterborne primer for fibre cement roofs, especially suitable for older very absorbent roof plates. Eternit Primer penetrates into the fibre cement plate and ensures good adhesion of the topcoat. Eternit Primer should always be overcoated with Isonit 12, 20, 50 or Rubber. Rubber is especially recommended for degraded primed fibre cement plates.



TIKKURILA

ETERNIT PRIMER

TECHNICAL DATA

Colour Shades	Available in factory ready made shades: Anthracite Grey Dark, Black and Red Brown
Gloss	Full matt. -
Coverage	5-7 m ² /l (1 layer) The practical spreading rate depends on application method, form and surface of the material.
Can sizes	10 l
Application method	Brush, roller or airless, nozzles 19 – 21, pressure 180 - 220 bar.
Drying time (23°C and 50% relative air humidity)	The drying time for wet layer thickness 200 µm 20° C / 65 % RH: Recoatable after 1 hour. The drying time depend on layer thickness, temperature, relative air humidity, and air circulation.
Density (kg/l)	1,2
VOC	Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations. Recycle or dispose of empty, dry cans in accordance with local regulations. VOC: Max. 30 g/l (Kat. A/h)
Storage	Protect from frost and direct sunlight. Close can carefully for next use. Store in a cool place, protected from frost in tightly closed original containers, and out of reach for children.

ETERNIT PRIMER

APPLICATION INSTRUCTIONS

Application conditions

The temperature must be between 8° C and 30° C and relative humidity <85 % RH.

Surface preparation

Roofs to be primed with Eternit Primer should be thoroughly cleaned using high-pressure washer and Iso A-Clean.

Application

To ensure the optimum layer thickness, apply the paint in two layers. Allow sufficient drying time between applications.

Always make a test coat to ensure the compatibility of product and surface.

Cleaning of tools

Clean the tools with water and soap Clean tools with water and detergent.

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Harmful to aquatic life with long lasting effects. Contains 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)) and 2-octyl-2H-isothiazol-3-one (OIT). May produce an allergic reaction. Avoid release to the environment. Wear protective gloves. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.