



TIKKURILA

## EURO EXTRA 20

EURO EXTRA 20 - WASHABLE PAINT FOR WET PREMISES

- DESCRIPTION** Waterborne paint for walls and ceilings inside premises with moderate and high maintenance.
- RECOMMENDED USES** Suitable for painting previously painted and unpainted surfaces such as: plasterboards, brick, gypsum boards, wallpapers, filler-treated, chipboard and wood-fiber plates inside premises with moderate and high maintenance (kitchens, bathrooms, laundries, etc), suitable for painting radiators. Resistant to steam from household appliances (kettle, steamer) and condensation, protects from mold. Can be used in child welfare institutions and facilities of the administrative group of medical institutions.
- PRODUCT FEATURES** Suitable for painting walls and ceilings in wet premises, including bathrooms, kitchens, laundries.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

## EURO EXTRA 20

TECHNICAL DATA	
<b>Base paints</b>	A BASE, C BASE
<b>Colour Shades</b>	To tint in pastel and bright colors, use Tikkurila tinting service. Base A can be used as white paint or tinted to light interior colours. While painting in bright C-base colors, it is recommended to apply a coat of A-base paint, tinted in close color. Base C can be used only in tinted form.
<b>Gloss</b>	Semi-matt. Semi Matt
<b>Coverage</b>	6-8 m <sup>2</sup> /l on rough absorbent surface. 9-11 m <sup>2</sup> /l on smooth non-absorbent surface.
<b>Can sizes</b>	A BASE: 0.9 l, 2.7 l, 5 l, 9 l C BASE: 0.9 l, 2.7 l, 5 l, 9 l
<b>Thinner</b>	Water
<b>Application method</b>	Brush, roller or spray.
<b>Drying time (23°C and 50% relative air humidity)</b>	Drying time (20±2°C) and relative air humidity (65±5%): recoatable after 4 hours. The specified level of stability of the coating to wash is achieved after 4 weeks.
<b>Density (kg/l)</b>	Approx. 1,1-1,3 kg/l depending on shade
<b>Wash resistance</b>	The paint forms a coating resistant to repeated intensive washing with the use of household non-abrasive detergents.
<b>Wet scrub resistance</b>	SFS-EN 13300 class I, ISO 11998.
<b>Volume solids (%)</b>	Approx. 46% depending on color shade.
<b>VOC</b>	Contains VOC max. 30 g/l.
<b>Storage</b>	Protect from frost. Store and transport at temperature above 5 °C in tightly closed package, protecting from moisture, heat and direct sunlight. Warranty storage period in unopened original package – 36 months.

# EURO EXTRA 20

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry and clean, the ambient temperature at least +5 °C and the relative humidity of air below 80%.

### Mixing components

If necessary, thinning with water no more than 5% by volume in case of application by brush or roller, no more than 10% by volume in case of application by spray.

### Surface preparation

Unpainted surfaces:

Clean the unpainted surfaces of any dirt, dust and fat. Rough and absorbent surfaces is recommended to primed with primers Euro Primer. In case of continuous filler, priming is not required. Priming is mandatory before application on rough absorbent surfaces and surfaces filled with drymixtures. Surfaces with mold, moss etc. are cleaned with Homeenpoisto in accordance with the instructions. When applied to radiators, pre-primed with Rostex primer.

Previously painted surface:

Remove any flaking, chalky and poorly adhering paint coats. Sand the surface, remove the sanding dust. Surfaces with mold, moss etc. are cleaned with Homeenpoisto in accordance with the instructions. Chalk whitewash or lime paint completely removed, then clean the surface with water and detergent Maalipesu, and then with clean water and let it dry. Fill any holes and cracks and level the surface with filler Euro Fille in rooms with high humidity or Euro Filler Light in dry rooms. Let the filler dry, sand the surface, remove the sanding dust and prime with primers Euro Primer.

Stir the paint well before use. Delute with water If necessary in accordance with the information in p. Product Mixing Components. To avoid differences in shades, use paint of the same rproduction batch. Apply the paint in 2 coats.

### Cleaning of tools

Clean tools with water. Remove lightly hardened paint with detergent.

### Maintenance instructions

If needed, after approx. 1 month from treating the surface, at the earliest.

Clean the surfaces with a neutral (pH 6–8) cleaning solution and e.g. a sponge or cleaning cloth. Clean very dirty surfaces with a mild alkaline (pH 8–10) cleaning solution and e.g. a cleaning cloth or sponge. After washing, rinse the surface thoroughly. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

After surface treatment, surfaces must be handled with care for a few weeks, as the product will reach its final hardness and durability after about a month under normal conditions.

If the surfaces need to be cleaned soon after finishing, clean them lightly with a damp cleaning cloth.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.