

TIKKURILA

EURO SMART 2

EURO SMART 2 - INTERIOR PAINT FOR WALLS AND CEILINGS.



DESCRIPTION Waterborne paint for walls and ceilings.

RECOMMENDED USES Suitable for painting previously painted and unpainted walls and ceilings inside dry premises, on

concrete, brick, plastered surfaces, filler-treated, gypsum plasterboard, particle board and wood-

fiber plates.

Can be used in child welfare institutions and facilities of the administrative group of medical

institutions.

PRODUCT FEATURES Suitable for painting walls and ceilings inside dry premises.



TECHNICAL DATA

Base paints A BASE

Colour Shades For tinting to pastelcolors, use Tikkurila tinting service.

Base A can be used as white paint.

Gloss Full matt. FM

Coverage 10-12 m²/l on smooth non-absorbent surface;

7-9 m²/l on rough absorbent surface.

Can sizes 0.9 l, 2.7 l, 9 l

Thinner Water.

Application method Brush, roller or spray.

Drying time (23°C and 50% relative air humidity)

Drying time (20 \pm 2°C) and relative air humidity (65 \pm 5%): recoatable after 2 hours. The specified level of stability of the coating to wash is achieved after 4 weeks. After

washing, a slight change in the gloss of the coating is allowed.

Density (kg/l) Approx. 1,4-1,5 kg/l.

Permeability to CO2 (EN

1062-6)

False

Wash resistance Resistant to easy washing with a soft foam rubber sponge. After washing, a slight

change in the gloss of the coating is allowed.

Wet scrub resistance SFS-EN 13300 class III, ISO 11998.

Volume solids (%) about58% depending of the color.

VOC Contains VOC max. 1 g/l.





Storogo	Protect from the frost. Store and transport at temperature above 5 °C in tightly
Storage	closed containers, protecting against moisture, heat and direct sunlight. Warranty
	storage period in unopened original package – 36 months.



APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry and clean , the temperature at least 5°C and the relative humidity of the air not more than 80%.

Mixing components

If necessary, thinning with water no more than 5% by volume in case of application by brush or roller, no more than 10% by volume in case of application by spray.

Surface preparation

Unpainted surfaces:

Clean the unpainted surfaces of any dirt, dust and fat. Rough and absorbent surfaces is recommended to primed with primers Tikkurila Euro Primer. In case of continuous filler, no priming is required. Priming is mandatory before application onrough absorbent surfaces and surfaces filled with dry construction mixtures.

Previously painted surface:

Remove any flaking, chalky and poorly adhering paint coats. Sand the surface, remove the sanding dust. Whitewash or lime paint completely removed, then clean the surface with water and detergent Tikkurila Maalipesu, after that washed with clean water and let it dry. Fill any holes and cracks and level the surfaces with filler Tikkurila Euro Filler or Euro Filler Light. Let the filler dry, sand the surfaces, remove the sanding dust and primed with primers Tikkurila Euro Primer.

Stir the paint well before use. If necessary, thinning with water no more than 5% by volume in case of application by brush or roller, no more than 10% by volume in case of application by spray. Reserve enough paint from the same production batch for a uniform color of surface. Apply the paint in 2 coats.

Note

Composition

Cleaning of tools

Clean tools with water. Remove lightly hardened paint with detergent Tikkurila Pensselipesu.

Maintenance instructions

If needed, after approx. 1 month from surface treatment, not the earliest. Clean the surfaces with water, using soft sponge. After cleaning, the surface should not remain wet.

The surfaces must be handled with care for a few weeks, as the product will reach its final hardness and durability in about one month under normal conditions. If the surfaces need cleaning soon after the surface treatment, clean lightly by using a soft dry or wet sponge.

About the Google Translate Community
About GoogleRules and Guidelines Help Submit a Review





About the Google Translate Community
About GoogleRules and Guidelines Help Submit a Review