



TIKKURILA  
**FEELINGS EXTRA DURABLE**  
WASH-RESISTANT SEMI-MATT PAINT

- DESCRIPTION** Waterborne acrylate latex finishing paint for use on interior walls and ceilings.
- RECOMMENDED USES** Interior walls and ceilings in premises in which high wash and wear resistance is required such as lobbies, staircases, hospital corridors, patient rooms and other surfaces which are subject to higher than normal stress. The product has an approval for indirect contact in food industry (Finnish Food Act 23/2006).
- PRODUCT FEATURES** Interior painting of concrete, plaster, fillertreated, brick, cardboard, chipboard and wood fibre board surfaces. Suitable for both new and previously painted surfaces.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

## FEELINGS EXTRA DURABLE

TECHNICAL DATA	
Base paints	A BASE, C BASE
Colour Shades	Can be tinted in Tikkurila colors
Gloss	Semi-matt.
Coverage	Non-absorbent surfaces: 10–12 m <sup>2</sup> /l. Absorbent surfaces: 8–9 m <sup>2</sup> /l.
Can sizes	A BASE: 0.9 l, 2.7 l, 9 l C BASE: 0.9 l, 2.7 l, 9 l
Application method	Brush, roller or spray application. Thinning: if necessary thin by up to 5% with water.
Drying time (23°C and 50% relative air humidity)	Normally touch-dry in two hours and recoatable after four hours. Final hardness will be achieved after 2-3 days.
Density (kg/l)	1.2 kg/l, ISO 2811
Chemical resistance	Withstands solvents, e.g. white spirit
Wash resistance	Very good. Withstands also washing with cleaning detergents and disinfectants used in hospitals
Wet scrub resistance	SFS-EN 13300 Class I, ISO 11998
Heat resistance	85 °C (ISO 4211-2 and ISO 4211-3)
Volume solids (%)	40
VOC	(cat A/a) 30g/l (2010) Product contains max 30 g/l VOC.
Storage	Protect from frost

# FEELINGS EXTRA DURABLE

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry, the temperature of the air at least +5 °C, and the relative humidity of the air below 80 %.

### Surface preparation

Unpainted surface:

Remove dirt and dust from the unpainted surfaces. If necessary, fill holes and cracks with suitable Tikkurila Presto filler. Sand the filler and remove sanding dust. Prime with Feelings Universal Primer.

Previously painted surface:

Wash down previously painted surfaces with Cleaning Agent (Maalipesu) according to instructions of use and let dry. Remove loose, flaking paint with a scraper. Sand hard, glossy surfaces to a matt finish and remove sanding dust. Fill holes and cracks with a suitable Tikkurila Presto filler. Sand the filler and remove sanding dust. Prime with Feelings Universal Primer, if necessary.

### Application

Stir Feelings Extra Durable well before use. Apply two finishing coats by brush, roller or spray.

### Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

### Maintenance instructions

Cleanse the surfaces with neutral (pH 6 - 8) detergent using soft brush, sponge or cloth at the earliest 1 month after painting. Very dirty surfaces can be cleansed with lightly alkaline (pH 8 -10) detergent using e.g. a cleaning cloth or sponge. Rinse the surfaces carefully after cleaning. Follow the dilution instructions of the detergent manufacturer.

The product achieves its final hardness and durability after one month under normal conditions, therefore the surfaces must be handled with care during this time. If the surfaces need to be cleaned soon after finishing, clean them lightly with a soft brush or damp cleaning cloth.

### Maintenance treatment

Surfaces painted with Feelings Extra Durable can be repainted with same kind of waterborne paint. See Preparation.

### Environmental and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

### HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Harmful to aquatic life with long lasting effects. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. Avoid release to the environment. Wear protective gloves. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.