



TIKKURILA
FEELINGS FURNITURE PRIMER
PRIMER FOR FURNITURE PAINT

- DESCRIPTION** Low-odour waterborne acrylate primer
- RECOMMENDED USES** Suitable for doors, cabinets, furniture, window frames, skirtings, radiators, sheet metal wood stoves, etc.
- PRODUCT FEATURES** For use on interior substrates. Offers good adhesion, opacity and grain-filling properties, and provides a first-class foundation for subsequent coats of Feelings Furniture Paint. Feelings Furniture Primer can be used for repainting interior surfaces previously coated with waterborne, alkyd or acid catalysed paints.
Not suitable for repainting of surfaces previously coated with products including nitrocellulose.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

FEELINGS FURNITURE PRIMER

TECHNICAL DATA	
Base paints	A BASE
Colour Shades	Color cards: Feel the Color, Symphony Color System. Light shades can be tinted in Tikkurila colors.
Gloss	Matt.
Coverage	6-8 m ² /l per coat. The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.
Can sizes	0.9 l
Thinner	Water
Application method	Brush, roller or spray application. Polyester and nylon paint brushes are best suited for the application of Feelings Furniture Primer. For airless spray use a 0.013" – 0.015" spray tip. Thinning: if necessary thin by up to 10-5 % with water.
Drying time (23°C and 50% relative air humidity)	Touch dry after approx. 1 hour. Recoatable with Feelings Furniture Primer approximately after 2 hours. Recoatable with Feelings Furniture Paint approximately after 5 hours.
Density (kg/l)	Approx. 1.3 kg/l
Volume solids (%)	35
VOC	(cat A/g) 30g/l(2010) Feelings Furniture Primer contains VOC max. 30 g/l
Storage	Protect from frost

FEELINGS FURNITURE PRIMER

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the temperature of the air at least +8 °C, and the relative humidity of the air below 80%. Lower temperature (approx. +15 °C) and higher humidity (50-70 % RH) will make the open-time of the paint longer and the work easier.

Surface preparation

Remove all dirt and dust carefully to obtain good adhesion.

Wash down previously painted or lacquered surfaces with Maalipesu Cleaning Agent and rinse carefully with water. Let dry. Remove loose, flaking paint or lacquer with a scraper and sand the whole surface. Remove sanding dust. Fill holes and cracks with Presto Rapid Filler and sand the filled parts. Remove sanding dust.

Stir Feelings Furniture Primer well before use and thin with water, if necessary. Apply by brush, roller, paint pad, or spray.

Apply on large surfaces with e.g. a furniture paint roller and then level with a brush.

Multi-branched synthetic brushes are best suited for the work.

Prime absorbent surfaces first with primer thinned with 5-10 % water, and sand. After 2 hours paint the surface with unthinned primer.

Finishing can be done after 5 hours with Feelings Furniture Paint.

Cleaning of tools

Remove excess paint/ lacquer from tools and clean with water. Tikkurila Pensselipesu (Tool Cleaner) is recommended to be used to remove a bit hardened paint.

Maintenance instructions

If needed, at the earliest after approx. 1 month from painting: Clean the surface with a neutral (pH 6-8) diswashing liquid and with soft brush, sponge or cleaning cloth. Clean very dirty surfaces with a lightly alkaline (pH 8-10) diswashing liquid and with cleaning cloth or sponge. Rinse the surface carefully.

The surfaces must be handled with care during few weeks after finishing, because the paint will reach its final hardness in normal circumstances after one month. If the surfaces need to be cleansed soon after finishing they must be cleansed lightly with a soft brush or slightly moist cleaning cloth.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.