



TIKKURILA  
**FEELINGS INTERIOR PAINT**  
FULL MATT INTERIOR PAINT

**DESCRIPTION** Waterborne acrylate paint

**RECOMMENDED USES** For use on interior walls and ceilings.

**PRODUCT FEATURES** Full-matt low-odour waterborne acrylate paint for use on interior walls and ceilings. Offers good wash-resistance. Suitable for plaster, concrete, filler treated, brick, cardboard surfaces, also for card-boarded gypsum board, chipboard and wooden fibre board surfaces. Suitable for new and previously painted surfaces. Not suitable for painting doors or furniture.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# FEELINGS INTERIOR PAINT

TECHNICAL DATA	
<b>Base paints</b>	A BASE, C BASE
<b>Colour Shades</b>	<b>Color cards:</b> Deco Grey colour card, Deco Grey Opaques. Can be tinted in Tikkurila colors
<b>Gloss</b>	Full matt.
<b>Coverage</b>	10-12 m <sup>2</sup> /l for non-absorbing surfaces 8-9 m <sup>2</sup> /l for absorbing surfaces The above should be used as a guide, as actual spreading rates will depend upon many factors including texture, porosity and application method.
<b>Can sizes</b>	A BASE: 0.9 l, 2.7 l, 9 l C BASE: 0.9 l, 2.7 l, 9 l
<b>Application method</b>	Brush, roller or spray application. For airless spray use a 0.017" – 0.021" spray tip. Thinning: if necessary thin by up to 10% with water.
<b>Drying time</b>	Normally touch-dry in ½ hour and recoatable after 1-2 hours.
<b>Density (kg/l)</b>	Approx. 1.3 kg/l, depending on shade, ISO 2811
<b>Chemical resistance</b>	Resists cleaning chemicals and weak solvents, such as White Spirit.
<b>Wet scrub resistance</b>	Wet scrub resistance SFS-EN 13300 class II, (ISO 11998).
<b>Heat resistance</b>	85°C, ISO 4211-2 and ISO 4211-3
<b>Volume solids (%)</b>	40
<b>VOC</b>	(cat A/a) 30g/l (2010) Product contains max 30 g/l VOC
<b>Storage</b>	Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# FEELINGS INTERIOR PAINT

## APPLICATION INSTRUCTIONS

### Application conditions

All surfaces to be painted must be dry, the temperature of the air at least +5°C and the relative humidity of the air below 80%.

### Surface preparation

Unpainted surfaces:

Remove all dirt and dust. If necessary, smooth the surface with a suitable Tikkurila Presto filler and sand the dried surface. Remove sanding dust. Prime with e.g. Feelings Universal Primer.

Previously painted surfaces:

Wash down previously painted surfaces with Maalipesu Cleaning Agent and rinse carefully with water. Sand hard or glossy surfaces to a matt finish and remove sanding dust. Fill holes and cracks with a suitable Presto filler and sand the dried surface. Remove sanding dust. Prime the surface with e.g. Feelings Universal Primer before coating, if necessary.

### Application

Stir Feelings Interior Paint well before use and thin with water, if necessary. Apply one or two coats with a roller, brush or spray.

### Cleaning of tools

Clean the tools with water and soap Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

### Maintenance instructions

Earliest 1 month after treatment:

The surfaces can be cleaned with a dry brush, mop or cloth. Dirty surfaces can be cleaned with a neutral (pH 6-8) detergent using a damp cleaning equipment.

The surface must not be left wet after cleaning. Follow the instructions of the manufacturer for the detergent solution.

The product will achieve its final hardness and durability under normal conditions after 1 month, therefore the surfaces must be handled with care during this time. If the surfaces must be cleaned soon after treatment, use a dry or damp cloth or mop.

### Maintenance treatment

Surfaces treated with Feelings Interior Paint can be maintained with Feelings Interior Paint or a similar water-borne paint.

### Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Minimise paint wastage by estimating how much paint you will need. Reuse of paint can effectively minimise the products' life cycle environmental impact. Recover unused paint for re-use.

### Health and Safety

Wear protective gloves. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.