Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU)

2015/830 - Europe

Date of issue/ Date of Date of previous issue 11/22/2021 : 4/24/2019 revision



SAFETY DATA SHEET

FONTEFLOOR EP 100

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

: FONTEFLOOR EP 100 **Product name**

Product description : A two-component waterborne epoxy paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor

Tikkurila Oyi P.O. Box 53 FI-01301 VANTAA **FINLAND**

Telephone +358 20 191 2000

e-mail address of person : Tikkurila Oyj, responsible for this SDS Product Safety,

e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number : 112

(24h)

Supplier or Manufacturer

: Tikkurila Oyi Telephone number

+358 20 191 2000 (GMT +2) Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms



Signal word : Danger

Hazard statements : H318 - Causes serious eye damage.

H315 - Causes skin irritation.

H412 - Harmful to aquatic life with long lasting effects.

Version: 4 1/10

Precautionary statements

General : Not applicable.

Prevention: P280 - Wear protective gloves/clothing and eye/face protection.

P273 - Avoid release to the environment.

Response : P305 + P351 + P338, P310 - IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or physician.

Storage : Not applicable.

Disposal : Not applicable.

Hazardous ingredients : polyoxypropylenediamine

benzaldehyde, reaction products with diethylenetriamine and triethylenetetramine,

hydrogenated

Supplemental label

elements

: Contains m-phenylenebis(methylamine) and 1-((2-((2-aminoethyl)amino)ethyl)amino)

-3-phenoxypropan-2-ol. May produce an allergic reaction.

Marning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

2.3 Other hazards

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

			<u>Classification</u>	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
polyoxypropylenediamine	REACH #: 01-2119557899-12 CAS: 9046-10-0	≤2.6	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412	-
benzaldehyde, reaction products with diethylenetriamine and triethylenetetramine, hydrogenated	REACH #: 01-2120831939-40 CAS: 1219458-07-7	≤2.3	Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411	-
benzyl alcohol	REACH #: 01-2119492630-38 EC: 202-859-9 CAS: 100-51-6	≤3	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Irrit. 2, H319	-
1-methoxy-2-propanol	REACH #: 01-2119457435-35 EC: 203-539-1 CAS: 107-98-2 Index: 603-064-00-3	≤3	Flam. Liq. 3, H226 STOT SE 3, H336	-
Phenol, 4,4'- (1-methylethylidene)bis-, polymer with N1,N2-bis(2-aminoethyl)-1,2-ethanediamine, 2-(chloromethyl)oxirane and α- hydro-ω- hydroxypoly(oxy-1,2-ethanediyl), reaction products with glycidyl o-tolyl ether	CAS: 362679-94-5	≤3	Eye Dam. 1, H318	-
m-phenylenebis(methylamine)	REACH #: 01-2119480150-50 EC: 216-032-5 CAS: 1477-55-0	≤0.3	Acute Tox. 4, H302 Acute Tox. 4, H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412	-
1-((2-((2-aminoethyl)amino)ethyl) amino)-3-phenoxypropan-2-ol	REACH #: 01-2119971579-18 EC: 279-873-7 CAS: 82001-48-7	≤0.3	Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	-

Version : 4 2/10

Date of issue/Date of revision	22.11.2021 Date of previous issue	24.04.2019.	FONTEFLOOR EP 100	
		text	Section 16 for the full of the H statements lared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

SECTION 4: First aid measures

4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Show this

safety data sheet or label to the doctor if possible.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 20 minutes.

Get medical attention immediately.

Inhalation: Remove to fresh air.

Skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser. Do

NOT use solvents or thinners.

Ingestion : If accidentally swallowed rinse the mouth with plenty of water (only if the person is

conscious) and obtain immediate medical attention. Remove to fresh air and keep

at rest in a position comfortable for breathing. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye damage.

Causes skin irritation.

See Section 11 for more detailed information on health effects and symptoms.

Contains:

m-phenylenebis(methylamine)

May produce an allergic reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, CO₂, powders or water spray/mist.

Unsuitable extinguishing media

: Do not use a direct water jet that could spread the fire.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous combustion products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Version : 4 3/10

Date of issue/Date of revision	22.11.2021 Date of previous issue	24.04.2019.	FONTEFLOOR EP 100	

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Provide adequate ventilation. Avoid breathing vapor or mist. Avoid contact with skin and eyes. See Section 8 for information on appropriate personal protective equipment.
- **6.2 Environmental** precautions
- : Hazardous to aquatic environment. Do not allow to enter drains, water courses or
- 6.3 Methods and materials for containment and cleaning up
- : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
- 6.4 Reference to other sections
- : See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
- Kvoid contact with skin and eyes. Avoid breathing vapor. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.
- 7.2 Conditions for safe storage, including any incompatibilities
- : Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C ...+25°C. Do not allow to freeze. Store in accordance with local regulations.
- 7.3 Specific end use(s) : None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
☐-methoxy-2-propanol	EU OEL (Europe, 10/2019). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 100 ppm 8 hours. TWA: 375 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 568 mg/m³ 15 minutes.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Version: 4

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn (see Personal protection for both components). Provide a readily-accessible eyewash facility. Comply with the health and safety at work laws.

Individual protection measures

: Wear eye/face protection (EN166). Eye/face protection

Hand protection : Wear protective gloves. Gloves should be replaced regularly and if there is any

sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be

followed.

Recommended glove material (EN374):

< 1 hour (breakthrough time): nitrile rubber, butyl rubber

> 8 hours (breakthrough time): laminated foil

Not recommended: PVC or natural rubber (latex) gloves

Skin protection : Wear suitable protective clothing.

: If ventilation is inadequate, use respirator that will protect against dust/mist. Wear Respiratory protection

a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/certified respirator or equivalent. Check that mask fits

tightly and change filter regularly.

Environmental exposure

controls

: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid. Color : Coloured Odor : Strong.

Odor threshold : Not relevant for the hazard assessment of the product. pН : Not relevant for the hazard assessment of the product.

Melting point/freezing point Initial boiling point and

boiling range

: Not available. : Not available.

: >100 °C Flash point

Evaporation rate : Not available.

Flammability (solid, gas) : Not applicable. Product is a liquid.

Upper/lower flammability or

explosive limits

: Not available.

: Not available. Vapor pressure : Not available. Vapor density **Density** : 1.4 g/cm³

: Miscible in water. Solubility(ies) Partition coefficient: n-octanol/ : Not applicable.

water

Auto-ignition temperature : Not available.

Decomposition temperature : Not relevant for the hazard assessment of the product. **Viscosity** : Not relevant for the hazard assessment of the product.

Explosive properties : No explosive ingredients present. Oxidizing properties : No oxidizing ingredients present.

Particle characteristics

Median particle size : Not applicable.

Version : 4

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : See Section 10.5.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : Avoid extreme heat and freezing.

10.5 Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents strong acids strong alkalis

10.6 Hazardous decomposition products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure by inhalation may cause respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
penzyl alcohol	LC50 Inhalation Dusts and mists	Rat	4.178 mg/l	4 hours
	LD50 Oral	Rat	1230 mg/kg	-
m-phenylenebis (methylamine)	LC50 Inhalation Dusts and mists	Rat	1.34 mg/l	4 hours
	LC50 Inhalation Vapor	Rat	2.4 mg/l	4 hours
	LD50 Oral	Rat	930 mg/kg	-
1-((2-((2-aminoethyl)amino) ethyl)amino) -3-phenoxypropan-2-ol	LD50 Oral	Rat	301 mg/kg	-

Not classified.

Irritation/Corrosion

Causes skin irritation. Causes serious eye damage.

Sensitization

Not classified.

The product contains sensitizing substances mentioned in sections 2 and 3.

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

Version : 4 6/10

Teratogenicity

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

Aspiration hazard

Not classified.

SECTION 12: Ecological information

Ecological testing has not been conducted on this product.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008.

Harmful to aquatic life with long lasting effects.

Do not allow to enter drains, water courses or soil.

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
olyoxypropylenediamine	EC50 80 mg/l	Daphnia	48 hours
	LC50 16 mg/l	Fish	96 hours
m-phenylenebis (methylamine)	Acute EC50 12 mg/l	Algae - Scenedesmus subspicatus	72 hours
	Acute EC50 15.2 mg/l	Daphnia	48 hours
	Acute LC50 75 mg/l	Fish	96 hours
	Acute LC50 87.6 mg/l	Fish	96 hours
	Chronic NOEC 4.7 mg/l	Daphnia	21 days
1-((2-((2-aminoethyl)amino) ethyl)amino) -3-phenoxypropan-2-ol	NOEC 0.66 mg/l	Fish	96 hours

12.2 Persistence and degradability

Product/ingredient name	Test	Result		Dose		Inoculum
olyoxypropylenediamine	-	0 % - Not re	eadily - 28 days	-		-
Product/ingredient name	Aquatic half-life		Photolysis		Biodeg	radability
olyoxypropylenediamine	-		-		Not rea	dily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	Bioconcentration factor [BCF]	Potential
n-phenylenebis (methylamine)	0.18	2.69	low
1-methoxy-2-propanol	<1	3.16	low
benzyl alcohol	0.87	1.37	low

12.4 Mobility in soil

Version : 4 7/10

Soil/water partition

coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal

: Empty packaging should be recycled or disposed of in accordance with national

regulations.

Special precautions

: No additional information.

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in

the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Version: 4

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

Europe inventory: At least one component is not listed.

Persistent Organic Pollutants

Not listed.

VOC Directive : This product is in scope of Directive 2004/42/CE.

15.2 Chemical Safety

Assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification Justification

Skin Irrit. 2, H315

Eye Dam. 1, H318

Calculation method

Aquatic Chronic 3, H412

Calculation method

Full text of abbreviated H

statements

: F226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H332 Harmful if inhaled.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Full text of classifications

[CLP/GHS]

: Acute Tox. 4 ACUTE TOXICITY - Category 4

Aquatic Acute 1 AQUATIC HAZARD (ACUTE) - Category 1
Aquatic Chronic 1 AQUATIC HAZARD (LONG-TERM) - Category 1
Aquatic Chronic 2 AQUATIC HAZARD (LONG-TERM) - Category 2
Aquatic Chronic 3 AQUATIC HAZARD (LONG-TERM) - Category 3

Eye Dam. 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2

Flam. Liq. 3 FLAMMABLE LIQUIDS - Category 3

Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B Skin Corr. 1C Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1 SKIN SENSITIZATION - Category 1

STOT SE 3 SPECIFIC TARGET ORGAN TOXICITY (SINGLE

EXPOSURE) - Category 3

Date of issue/ Date of

revision

: 11/22/2021

Version : 4 9/10

Date of previous issue : 4/24/2019

Version : 4

Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 830/2015 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Version : 4 10/10