



Fontefloor PU Cem Primer

DESCRIPTION A solvent-free, water-borne hybrid polyurethane concrete primer.

PRODUCT FEATURES AND RECOMMENDED USES

- Due to low viscosity Fontefloor PU Cem Primer penetrates well into substrate.
- Adheres well to concrete and secures the adhesion of the subsequent layer. Adhesion to concrete is 2.7 N/mm²
- Used as a primer in Fontefloor PU Cem systems

TECHNICAL DATA

Volume solids 100%

Specific gravity 1.35 kg / l (mixture)

Mixing ratio	Fontefloor PU Cem Primer mixture	Fontefloor PU Cem 2 A 2.5KG
		Fontefloor PU Cem B 2.6KG
		Fontefloor PU Cem C 1.4KG

Pot life (+23°C) At +20°C: approx. 15 minutes

Practical coverage For a flat substrate:
Approximately 0.35–0.5 kg/m².
Practical coverage depends on the evenness of the substrate.

Drying time (+23°C) Foot traffic after 8 hours
Recoat after 12–48 hours
Fully cured after 7 days
At lower temperature the curing process will last longer.

Cleaning of equipment Cleaning of equipment with Thinner 1061. Equipment should be cleaned immediately after use before the primer has dried.

Finish Matt. Sunlight will affect on the shade and the gloss of the varnish in the long run.

Colors Red, green, buff, grey and crème.

Thinning instructions Do not thin Fontefloor PU Cem Primer.

VOC VOC 2004/42/EC (cat A/j) 140 g/l (2010)
Fontefloor PU Cem Primer: max. VOC < 140 g/l

Can sizes 3,0 L

Fontefloor PU Cem Primer

APPLICATION INSTRUCTIONS

Surface preparation	<p>New concrete Remove laitance by power grinding, vacuum grit blasting or hydrochloric acid etching. Choose the method best suited for the premises. After grinding remove dust carefully with a vacuum cleaner. Hydrochloric acid etching is carried out with diluted hydrochloric acid (1 part concentrated hydrochloric acid, 4 parts water). Rinse with plenty of water. Dry the floor.</p> <p>Old concrete Remove all grease, oil, chemicals and other impurities by Maalipesu detergent. Remove old peeling paint layer by grinding, milling or vacuum grit blasting. Choose the method best suited for the premises. Clean out pot-holes removing all loose friable material. Open cracks with e.g. an abrasive tool. Remove loose material and dust.</p> <p>Cementitious levelling screed Check compatibility with the levelling screed manufacturer.</p> <p>Polymer modified screed Check compatibility with the polymer modified screed manufacturer.</p>
Application conditions	<p>The relative humidity of the concrete should not exceed 97%. The temperature of the ambient air, surface or coating should be between +12°C–+25°C during either application or drying. Relative humidity of air should not exceed 80%.</p>
Mixing components	<p>Mix the correct proportions of the parts A and B thoroughly approx. 30 s by using a hand drill with a paddle, concrete mixer or power mixer. Add part C to the mixture and mix approx. 3 min until the mixture is homogenous. Ensure that the mixture is homogenous and use it immediately after mixing.</p> <p>Insufficient mixing or incorrect mixing ratio will result in uneven drying of the surface, weaken the properties of the screed and risk the success of the application.</p>
Priming	<p>Prime with unthinned Fontefloor PU Cem Primer. Pour the mixture onto the floor, apply with a long haired roller or rubber squeegee. Scatter sand of grain size 0.4–0.8 mm at approx. 150 g/m² on the fresh primer coat to ensure the screed adhesion and prohibit gliding of the screed.</p>
Patching	<p>Patch pot-holes and cracks with unthinned Fontefloor PU Cem 2 or Temafloor 400 epoxy varnish and dry, clean sand. Mixing ratio e.g. 1 part by volume of epoxy mixture or Fontefloor PU Cem 2 mixture and 1–2 parts by volume of sand of grain size Ø 0.1–0.6 mm. Sand the patched areas before overcoating, if necessary.</p>
Topcoating	<p>Overcoating should be done within 12–48 hours after priming. Pour the mixture onto the floor and apply with a trowel and level with a roller. To obtain a smoother surface and remove trowel marks the surface must be spike rolled.</p>
Storage	<p>Under cover and free of the ground, in dry conditions above +5°C and below +25°C. This is particularly important for the part C. Protect from frost even during transport.</p>
HEALTH AND SAFETY	<p>Containers are provided with safety labels, which should be observed. Further information about hazardous influences and protection are detailed in individual health and safety data sheets. A health and safety data sheet is available on request from Tikkurila Oyj.</p>



Fontefloor PU Cem Primer

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

The product is intended for professional use only and shall only be used by professionals who have sufficient knowledge and expertise on the proper use of the product. The information above is advisory only. To the extent permitted by applicable law, we shall not approve of any liability for the conditions under which the product is being used or for the use or application of the product.


In case you intend to use the product for any other purpose than that recommended in this document without first getting our written confirmation on the suitability for the intended use, such use takes place at your own risk.

Fontefloor PU Cem Primer

EN 13813:2002

The European harmonized product standard EN 13813:2002 defines the requirements for screed materials and floor screeds, including synthetic resin screeds.

This product is tested and CE-labelled in accordance with the tables ZA.1.5 and ZA.3.3 in the appendix ZA.3.

	
Tikkurila Oyj Kuninkaalantie 1 FI-01300 VANTAA	
17	
TIK-6627-5001b	
EN 13813:2002	
Synthetic resin screed.	
Impact resistance	IR4
Capillary absorption and permeability to water	NPD
Chemical resistance	NPD
Release of corrosive substances	SR
Abrasion resistance	≤AR1
Thermal resistance	NPD
Reaction to fire	E _{fl}
Adhesion strength by pull off test	≥B2,0
Release of dangerous substances	NPD
Sound absorption	NPD
Sound insulation	NPD


1) Tested as part of a system together with Fontefloor PU Cem 2 and Fontefloor PU Cem Top.

Fontefloor PU Cem Primer

EN 1504-2:2004

The European harmonized productstandard EN 1504-2:2004 defines the requirements for surface protection systems for concrete.

This product is tested and CE-labelled in accordance with the tables 1d, 1f and 1g in the appendix ZA.

	
Tikkurila Oyj Kuninkaalantie 1 FI-01300 VANTAA	
17	
TIK-6627-5001a	
EN 1504-2:2004	
Product for protection and repair of concrete structures – Coating.	
Permeability to CO ₂	$s_D > 50 \text{ m}$
Impact resistance	Class I: $\geq 4 \text{ Nm}$
Capillary absorption and permeability to water	$w < 0,1 \text{ kg/m}^2 \cdot h^{0,5}$
Abrasion resistance	$< 3000 \text{ mg}$
Reaction to fire	E_{fl}
Adhesion strength by pull off test	$\geq 2,0 \text{ N/mm}^2$
Release of dangerous substances	NPD
Permeability to water vapour	Class III, $s_D > 50 \text{ m}$
Resistance to severe chemical attack	Class II

1) Tested as part of a system together with Fontefloor PU Cem 2 and Fontefloor PU Cem Top.