



TIKKURILA

HARMONY KUVIOINTIMAALI

DESCRIPTION Translucent, full-matt acrylate-based effect paint.

RECOMMENDED USES Walls in residential, office and commercial spaces and similar dry spaces.

PRODUCT FEATURES For use in dry interior spaces on even surfaces which have been previously painted with Harmony interior paint.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



TIKKURILA

HARMONY KUVIOINTIMAALI

TECHNICAL DATA

| | |
|---|--|
| Base paints | CAP BASE |
| Colour Shades | Color cards: Symphony Color System, Feel the Color. |
| Gloss | Full matt. |
| Coverage | 13-18 m ² /l, depending on application method. |
| Can sizes | 0.9 l, 2.7 l |
| Application method | Apply with a roller and a brush. Patterning with effect roller, brush or other patterning tool. |
| Drying time (23°C and 50% relative air humidity) | Recoatable after approx. 24 hours. The surface is completely dry and ready to be taken into use in approximately two days. |
| Density (kg/l) | approx. 1.0 kg/l depending on shade, ISO 2811. |
| Wash resistance | Resists light wiping with a damp cloth. |
| Heat resistance | 85°C, ISO 4211-3. |
| Volume solids (%) | 12 |
| Storage | Protect from frost. |

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



HARMONY KUVIOINTIMAALI

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry; the temperature must be at least +10°C, and the relative air humidity 30-70%.

Surface preparation

Unpainted surfaces:

Clean new surfaces by removing any dirt and dust. Fill the surfaces with a suitable Tikkurila Spakkeli or Presto or Prestonit filler, if needed, and sand the dried surface. Remove sanding dust. Prime with Varma primer. Paint two times with Harmony interior paint.

Previously painted surfaces:

Wash previously painted surfaces with Maalipesu detergent and rinse carefully with water. Sand the hard and glossy painted surfaces non-glossy. Remove the sanding dust. Fill cracks and holes with Presto filler and sand the dried surface. Remove the sanding dust.

Paint with Harmony interior paint 1-2 times to desired color.

Painting

Mix Harmony Kuviointimaali carefully before use. Dilute with water 5-10 % if you wish to create a more glazed surface. Apply thinly using a roller. Finish immediately by rolling over the surface with an effect roller, brush or sponge. Work in approx. 1 meter wide strips. Practice effect painting first on a thick piece of cardboard or some other base.

Detailed instructions are available in Tikkurila's Effect Painting Guide.

Cleaning of tools

Clean tools with water. Remove excess paint/ lacquer from tools and clean with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint. Remove excess paint from tools. Clean tools with water. Tikkurila Pensselipesu (Tool Cleaner) is recommended to be used to remove a bit hardened paint.

Maintenance instructions

If needed, after approx. 1 month from treating the surface, at the earliest:

Surfaces can be cleaned with a dry brush or dust cloth. Any dirty surfaces can be cleaned with a neutral (pH 6–8) cleaning solution and a damp cleaning tool. The surface may not remain wet after cleaning. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

The product achieves its final hardness and durability after one month under normal conditions, and therefore the surfaces must be handled with care during this time. If the surfaces need to be cleaned soon after finishing, clean them lightly with a dry or damp cleaning cloth.

Maintenance treatment

With Harmony interior paint.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



HARMONY KUVIOINTIMAALI

Health and Safety

Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. Wear protective gloves. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.