



TIKKURILA  
**HELMI KALUSTEKITTI**

- DESCRIPTION** Water-borne special filler for furnitures.
- RECOMMENDED USES** Furniture, doors, windows and other wood surfaces in dry rooms.
- PRODUCT FEATURES** For filling small holes before applying a finishing coat. Suitable for both new and previously painted surfaces. Filling capacity 3mm.



## HELMI KALUSTEKITTI

### TECHNICAL DATA

<b>Colour Shades</b>	White
<b>Can sizes</b>	0.2 l
<b>Thinner</b>	Water
<b>Application method</b>	Apply with a smoothing trowel.
<b>Drying time (23°C and 50% relative air humidity)</b>	A thin layer, 1 mm, of filler can be sanded in approx. 1 hours.
<b>Density (kg/l)</b>	1,7 kg/l, ISO 2881
<b>Volume solids (%)</b>	74
<b>Storage</b>	Protect from frost and direct sunlight. Badly closed or short cans endure badly long-time storage.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



# HELMI KALUSTEKITTI

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be filled must be dry, the ambient temperature at least +10 °C and the relative humidity of air below 80%.

### Surface preparation

Unpainted surfaces:

Clean the surfaces of dirt. Remove any dust and loose material by brushing.

Previously painted surfaces:

Wash previously painted surfaces with Kalustepesu detergent. Once the surface is dry, remove as much paint as you can with a scraper and sand painted surfaces to a matte finish. Remove the sanding dust.

### Application

Apply Helmi Kalustekitti a smoothing trowel. Apply two or more coats of putty to large indentations if at all possible. Sand the surface and remove the sanding dust.

The surface can be finished with a water-borne or alkyd paint.

### Cleaning of tools

Clean tools with water.

### Environmental protection and waste disposal

Deliver empty packaging and hardened mortar to a recycling point or waste tip according to local regulations.

### Health and Safety

Contains 1,2-benzisothiazol-3(2H)-one (BIT). May produce an allergic reaction. Wear protective gloves.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.