



TIKKURILA  
**IKKUNAKITTI**

- DESCRIPTION** A traditional window putty made from special chalk and linseed oil.
- RECOMMENDED USES** For glazing and filling small cracks and crevices on wood surfaces.
- PRODUCT FEATURES** For filling small cracks and crevices on wood surfaces.



# IKKUNAKITTI

## TECHNICAL DATA

<b>Coverage</b>	For glazing, apply approx. 100 g/m.
<b>Can sizes</b>	0.3 l, 0.375 l, 3 l
<b>Application method</b>	Apply with a putty knife.
<b>Drying time</b>	Under normal conditions, the putty surface will be touch-dry in a few days.
<b>Density (kg/l)</b>	2.1 kg/l, ISO 2811
<b>Volume solids (%)</b>	100
<b>Storage</b>	Unaffected by cold storage or transportation.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# IKKUNAKITTI

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be treated must be dry, the temperature of the air at least +5 °C and the relative humidity of air below 80%.

### Surface preparation

Remove loose and flaky putty from the grooves with a smoothing scraper. Clean the surface with sand paper or a wire brush.

### Application

Prime the putty grooves with Valtti-Pohjuste and a single application of diluted Lin Pellavaöljymaali or Teho Öljymaali before applying the putty. Spread Ikkunakitti with a putty knife. You can achieve a smooth surface by dipping the putty knife in water before smoothing the putty. Apply two coats of window frame paint (for exterior surfaces, e.g. Lin Pellavaöljymaali or Teho Öljymaali) to the putty surface in a few days. The paint must extend 1–2 mm over the window pane.

### Cleaning of tools

Clean tools with White Spirit 1050.

### Environmental protection and waste disposal

Deliver empty packaging and hardened mortar to a recycling point or waste tip according to local regulations.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.