



TIKKURILA
LAKKABENSIINI 1050
WHITE SPIRIT

- DESCRIPTION** Aromatic-free white spirit.
- RECOMMENDED USES** Thinning
- PRODUCT FEATURES** Thinning alkyd paint and lacquer. Cleaning painting tools and removing grease from surfaces before painting (small areas).





LAKKABENSIINI 1050

TECHNICAL DATA

Can sizes	1 l, 3 l, 10 l
Density (kg/l)	0.78 kg/l, ISO 2811
Storage	Unaffected by cold storage or transportation.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

LAKKABENSIINI 1050

APPLICATION INSTRUCTIONS

See the products' directions for use for more information.

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Contains: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics. **Danger.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Store locked up. Repeated exposure may cause skin dryness or cracking.



GHS02



GHS07



GHS08

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.