



TIKKURILA

LASSEN PERUSPOHJUSTE



DESCRIPTION

Basic priming oil. Lassen Peruspohjuste is absorbed into wood and slows the effects of humidity.

RECOMMENDED USES

For exterior sawn and planed wood, log and impregnated wood surfaces.

PRODUCT FEATURES

For protection and priming of timber and wooden structures before surface treatment. Not suitable for the interior treatment of greenhouses. A colorless priming oil will not protect the wood surface from the adverse effects of sunlight.

LASSEN PERUSPOHJUSTE

TECHNICAL DATA

Colour Shades	Colorless.
Coverage	Sawn wood: 4–5 m ² /l. Planed wood and log surfaces: 8–10 m ² /l.
Can sizes	10 l
Thinner	Lakkabensiini 1050
Application method	Brush, dipping.
Drying time (23°C and 50% relative air humidity)	Touch-dry in approx. 30 minutes. The finishing coat can be applied after 24 hours.
Density (kg/l)	Approx. 0.8 kg/l, ISO 2811.
Volume solids (%)	10
Storage	Unaffected by cold storage or transportation. Badly closed or short cans endure badly long-time storage.

LASSEN PERUSPOHJUSTE

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry, the temperature of the air at least +5 °C and the relative humidity of the air below 80 % during treatment and drying.

Application

Treat wood surfaces with Lassen Peruspohjuste in the earliest possible phase of construction. Remove dirt, mold and any loose material from the surface to be treated. Protect plants from splashes.

Apply a generous coat of Lassen Peruspohjuste with a brush or by dipping. Treat the end grains of the wood with particular care.

Cleaning of tools

Clean tools with White Spirit 1050.

Environmental and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Contains: hydrocarbons, C9, aromatics, hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics. **DANGER.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. Contains 3-iodo-2-propynyl butylcarbamate (IPBC). May produce an allergic reaction. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from sparks and open flames. - No smoking. Avoid breathing vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. Do NOT induce vomiting. Wear protective gloves.



GHS02



GHS07



GHS08



GHS09

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.