



TIKKURILA

# LIN PELLAVAÖLJYMAALI

- DESCRIPTION** A traditional oil paint with linseed oil binder.
- RECOMMENDED USES** Exterior walls, window sashes, fences, doors, flagpoles.
- PRODUCT FEATURES** Outdoor painting of wood surfaces. Suitable for new wood, factory-primed surfaces or surfaces previously treated with oil paint. Outdoor painting of ornaments made of gypsum. See directions for use



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# LIN PELLAVAÖLJYMAALI

## TECHNICAL DATA

<b>Base paints</b>	AW BASE, CW BASE
<b>Colour Shades</b>	<b>Color cards:</b> Old times colors. Can be tinted in Tikkurila exterior colors.
<b>Gloss</b>	Semi-gloss.
<b>Coverage</b>	Sawn wood surfaces 8–12 m <sup>2</sup> /l. Planed wood surfaces 10–16 m <sup>2</sup> /l.
<b>Can sizes</b>	AW BASE: 2.7 l, 9 l CW BASE: 2.7 l, 9 l
<b>Application method</b>	Brush
<b>Drying time</b>	4–7 days depending on the conditions. Recoatable after the previous coat has dried.
<b>Density (kg/l)</b>	approx. 1.6 kg/l, ISO 2811
<b>Volume solids (%)</b>	95-98
<b>Storage</b>	Close can carefully for next use.

# LIN PELLAVAÖLJYMAALI

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry, the temperature at least +5°C and the relative humidity of the air below 80%. Avoid painting when rain is expected.

### Mixing components

Use Valtti Pohjuste Primer for the first application. For finishing coat thin with White Spirit 1050 or with Valtti Pohjuste Primer, if necessary.

### Surface preparation

Wash any dirty and moldy surfaces with Tikkurila Homeenpoisto. Remove loose material from previously painted surfaces with a scraper and clean the surface. Remove loose resin from knots.

### Priming

Prime new or bare wood surfaces with Valtti Pohjuste or Valtti Plus Base.

### Painting

Priming:

The surface to be treated must be clean and dust-free. Thin Lin Pellavaöljymaali 5–10 % with white spirit. Stir the paint well and apply thin layers by rubbing tightly to avoid wrinkling. Allow the surface to dry at least 4 days before finishing.

Finishing:

Stir the paint well before use and thin max. 5% with White Spirit, if necessary. Paint the end grains of the wood with particular care. If recoating is done after several weeks, roughen the smooth painted surface before painting.

Wood contains resin and other staining extracts, particularly around knots, which can cause discoloration or bleeding in the painted surface due to variations in temperature and humidity.

### Cleaning of tools

Clean tools with White Spirit 1050 or Tikkurila Pensselipesu (Tool Cleaner).

### Maintenance instructions

Handle the painted surface with care as the product achieves its final hardness and durability in about four weeks under normal conditions. The surface can be cleaned lightly about 4 days after treatment using a soft brush, a damp cleaning cloth or a mop.

After one month from painting, a dirty surface can be cleaned with Talon Huoltipesu (mix 1 part of Talon Huoltipesu with 10 parts of water). Clean stains and very dirty surfaces with a stronger solution of Talon Huoltipesu and water (1:1). After washing, rinse the surfaces and allow to dry.

### Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# LIN PELLAVAÖLJYMAALI

## Health and Safety

**Contains:** 2-octyl-2H-isothiazol-3-one (OIT), 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT). **Warning.** May cause an allergic skin reaction. Very toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Avoid breathing vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. **IF ON SKIN:** Wash with plenty of soap and water. Contains small amounts of sensitizing substances: cobalt bis(2-ethylhexanoate).



GHS07



GHS09

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.