



TIKKURILA
NASTA REMONTTIMAALI



DESCRIPTION Solvent-free renovation paint for interiors.

RECOMMENDED USES Interior walls and ceilings on dry premises.

PRODUCT FEATURES For interior painting of concrete, plaster, filler-treated, plasterboard, chipboard and wood fiberboard surfaces according to instructions. Also suitable for repainting previously painted surfaces.



NASTA REMONTTIMAALI

TECHNICAL DATA	
Base paints	C BASE
Colour Shades	Can be tinted in Tikkurila colors.
Gloss	Semi-matt.
Coverage	For absorbing surfaces 5-7 m ² /l. For non-absorbing surfaces 9-11 m ² /l.
Can sizes	2.7 l, 9 l
Application method	Brush, roller or spray. Airless spray application -nozzle 0.017"-0.021" -thinning 0-10% by volume.
Drying time (23°C and 50% relative air humidity)	Dust dry after half an hour. Recoatable after 1-2 hours.
Density (kg/l)	approx. 1.3 kg/l, ISO 2811.
Chemical resistance	Withstands cleaning chemicals and weak solvents, such as white spirit.
Wet scrub resistance	SFS-EN 13300 class II, ISO 11998
Heat resistance	85 °C, ISO 4211-3.
Volume solids (%)	40
Storage	Protect from frost. Badly closed or short cans endure badly long-time storage.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



NASTA REMONTTIMAALI

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the temperature at least +5°C and the relative humidity of the air below 80%.

Surface preparation

Unpainted surfaces:

Clean the surfaces by removing any dirt and dust. If needed, fill the surfaces with a suitable filler and sand the dried surface. Remove the sanding dust. Prime if needed.

Previously painted surfaces:

Wash previously painted surfaces with Seinäpesu detergent and rinse carefully with water. Sand the hard, glossy painted surfaces non-glossy. Remove the sanding dust. Fill any cracks and holes with a suitable filler and sand the dried surface. Remove the sanding dust. Prime if needed.

Painting

Stir Nasta well before use and thin with water, if necessary. Apply 1–2 coats by roller, brush or spray.

Cleaning of tools

Clean the tools with water and soap. Remove excess paint/ lacquer from tools and clean with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Maintenance instructions

Cleaning approx. 1 month after painting at the earliest, if needed.

Clean the surfaces with a neutral (pH 6–8) cleaning solution and e.g. a sponge or cleaning cloth. Clean very dirty surfaces with a mild alkaline (pH 8–10) cleaning solution and e.g. a cleaning cloth, mop or sponge. After washing, rinse the surface thoroughly. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

The product achieves its final hardness and durability after one month under normal conditions, and therefore the surfaces must be handled with care during this time. If the surfaces need to be cleaned soon after finishing, clean them lightly with a damp cleaning cloth or mop.

Maintenance treatment

Surfaces painted with Nasta can be recoated with the same or similar water-borne paint. See Pretreatment.

Environmental and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. Wear protective gloves. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.