

TIKKURILA

## NOVOFLOOR PAKSUNNIN



### DESCRIPTION

Thickening fibre, which is used for thickening of Novofloor, Novopox ja Novocryl coatings, when making baseboards and other vertical surfaces. Does not affect the tint of the coating.

### RECOMMENDED USES

When coating the floors of balconies, outdoor corridors, passenger corridors, etc.

### PRODUCT FEATURES

For coating baseboards and other vertical surfaces. Also suitable for levelling mortar with Novopox P epoxy primer.

For professional use only.

# NOVOFLOOR PAKSUNNIN

## TECHNICAL DATA

<b>Colour Shades</b>	White thickening fibre.
<b>Coverage</b>	0.5-3.0 p-%
<b>Can sizes</b>	1 kg
<b>Density (kg/l)</b>	approx. 0.96 g / cm <sup>3</sup>
<b>Storage</b>	In a cool and dry place.

# NOVOFLOOR PAKSUNNIN

## APPLICATION INSTRUCTIONS

### Application

The thickening fibre is added in stages to the primer or mixed with a machine to form a uniform pulp. Avoid high speed when mixing, as it forms air bubbles in the coating.

When adding the thickening fibre the levelling of the product and hence the appearance is affected. Thickening fibre may also increase the drying time.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.