

TIKKURILA

ÖLJYPOHJA

ALKYD PRIMER FOR EXTERIOR WOOD SURFACES

DESCRIPTION	Alkyd oil primer for outdoor painting of bare wood surfaces.
RECOMMENDED USES	Exterior walls, window sashes, railings, fences.
PRODUCT FEATURES	Alkyd oil primer for outdoor painting of bare wood surfaces before finishing with oil or acrylic paints. Also suitable for painting surfaces previously treated with oil paint. Also suitable for painting new and industrially painted surfaces, and surfaces previously treated with alkyd or oil paints.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

ÖLJYPOHJA

TECHNICAL DATA

Base paints	AP BASE
Gloss	Matt.
Coverage	Sawn surfaces 6-8 m²/l. Planed surfaces 8–12 m²/l.
Can sizes	0.9 l, 2.7 l, 9 l
Thinner	White spirit
Application method	Brush or spray and smooth with the brush.
Drying time	Recoatable after 6 hours. Drying time depends on conditions, absorbency of the substrate and paint film thickness.
Volume solids (%)	58
Storage	Unaffected by cold storage or transportation. Badly closed or short cans endure badly long-time storage.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

ÖLJYPOHJA

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry. This means that the moisture content of the wood is below 20%. During painting and drying, the temperature of the air must be at least +5°C and the relative humidity below 80%. Plan the work so that the paint film has time to dry before the evening dew.

Surface preparation

Unpainted surfaces:
Clean surfaces of any dirt, mold and loose material. Wash dirty and moldy surfaces with Tikkurila Homeenpoisto according to the instructions. Remove loose resin from knots. Prime surfaces at the earliest possible stage of construction with Valtti Pohjuste or Valtti Plus Pohjuste.

Previously painted surfaces:
Clean surfaces of any dirt, mold and loose material. Remove loose previous treatment, grey wood and resin from knots with a scraper. Brush the surface clean with a wire brush. Wash dirty and moldy surfaces with Tikkurila Homeenpoisto according to the instructions. Treat any bare wood surfaces with Valtti Pohjuste or Valtti Plus Pohjuste.

Painting

Stir Öljypohja well and apply on bare wood surfaces 1-2 times. Treat the end grains of the wood with particular care.
Finishing painting is recommended to be performed as soon as possible after priming.
Wood contains resin and other staining extracts, particularly around knots, which can cause discoloration or bleeding in the painted surface due to variations in temperature and humidity.
Suitable topcoats: Ultra series house paints, Pika-Teho, Teho Modern, Vinha and Unica Akva Maali.

Cleaning of tools

Clean tools with White Spirit 1050 or Tikkurila Pensselipesu (Tool Cleaner).

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Warning. Flammable liquid and vapor. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Dispose of contents and container in accordance with all local, regional, national and international regulations.



GHS02

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.