

## DECLARATION OF PERFORMANCE

### Finnseco Rappauskorjauslaasti Hieno

No. TIK-A062-2022

1. Unique identification code of the product type: **TIK-A062-2022 Finnseco Rappauskorjauslaasti Hieno**
2. Intended use: **General purpose rendering/plastering mortar (GP)**
3. Manufacturer: **Tikkurila Oyj, P.O. Box 53, FI-01301 Vantaa**
4. System of AVCP: **AVCP 4**
5. Harmonised standard: **EN 998-1:2016**
6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Dry bulk density	1.75-1.85 kg/dm <sup>3</sup>	EN 998-1:2016
Compressive strength	CS I	
Capillary water absorption	W <sub>c</sub> 0	
Water vapor permeability	NPD	
Thermal conductivity	≤ 0.2 W/m•K (table value)	
Reaction to fire	A1	
Long-term resistance to freeze-thaw stress	NPD	
Release of dangerous substances	No	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on the behalf of the manufacturer by:



Jani Rutanen  
RDI Manager, Mineral&Flooring, Technology&IPR

Vantaa 17.3.2022