## **DECLARATION OF PERFORMANCE**

## Temafloor PU Flex Color polyurethane coating

No TIK-A020-2018

- 1. Unique identification code of the product type: **TIK-A033-2019 Fontefloor PU Matt**
- 2. Intended uses: Product for protection and repair of concrete structures Coating: ingress protection (1.3), physical resistance (5.1)
- 3. Manufacturer: Tikkurila Oyj, Kuninkaalantie 1, Fl-01300 Vantaa
- 4. Systems of assessment and verification of consistency of performance of the construction product: **AVCP 2+ and AVCP 3**
- 5. Harmonised standard: **EN 1504-2:2004**

Notified body: AVCP 2+: 0809 VTT Expert Services Oy

AVCP 3: 0809 VTT Expert Services Oy (VTT-S-00094-16)

## 6. Declared performances:

| Essential characteristics                      | Performance                                  | Harmonised technical specification |
|--|--|------------------------------------|
| Linear shrinkage                               | NPD  |                                    |
| Compressive strength                           | NPD  |                                    |
| Coefficient of thermal expansion               | NPD  |                                    |
| Abrasion resistance                            | weight loss < 3000 mg                        |                                    |
| Adhesion by cross-cut test                     | NPD  |                                    |
| Permeability to CO <sub>2</sub>                | CO <sub>2SD</sub> > 50 m                     |                                    |
| Permeability to water vapour                   | class II, 5 m < s <sub>D</sub> < 50 m        |                                    |
| Capillary absorption and permeability to water | w < 0.1 kg/m <sup>2</sup> · h <sup>0,5</sup> |                                    |
| Adhesion after thermal compatibility           | NPD  | EN 1504-2:2004                     |
| Resistance to thermal shock                    | NPD  |                                    |
| Chemical resistance                            | NPD  |                                    |
| Resistance to severe chemical attack           | NPD  |                                    |
| Crack bridging ability                         | NPD  |                                    |
| Impact resistance                              | class III: ≥ 20 Nm                           |                                    |
| Adhesion strength by pull-off test             | ≥ 2.0 N/mm²                                  |                                    |
| Fire classification                            | E <sub>fl</sub> -s1*                         |                                    |
| Slip/skid resistance                           | NPD  |                                    |
| Behaviour after artificial weathering          | NPD  |                                    |
| Antistatic behaviour                           | NPD  |                                    |
| Adhesion on wet concrete                       | NPD  |                                    |
| Diffusion of chloride ions                     | NPD  |                                    |
| Release of dangerous substances                | NPD  |                                    |

<sup>\*</sup>Tikkurila Cozy Floor System: B<sub>fl</sub>-s1

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on the behalf of the manufacturer by:

Magnus Engblom

At Vantaa on 9.7.2019

dagns Eyl