



TIKKURILA

EVERAL THINNER 1050

DESCRIPTION

Tikkurila Everal Thinner 1050 is design to thin paints and varnishes based on alkyd resin. The product is good also for cleaning the painting tools and forcleaning the grease from the surface before painting it with alkyd products.

RECOMMENDED USES

Thinning of paints and varnishes till wanted viscosity, which facilitate the application with roller or brush. For cleaning of surface before interior and exterior painting.

PRODUCT FEATURES

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



EVERAL THINNER 1050

TECHNICAL DATA

Can sizes 1 l

Density (kg/l) 0,8

VOC The product is not subject to the regulation on the limitation of emissions of VOCs in certain paints and varnishes.

Storage Product is classified as a dangerous under a ADR/RID transport regulation, 3UN 1268 class. Bottles with 1L size are not taken under ADR consideration because they are packed in bulk packaging (cartoon).

EVERAL THINNER 1050

APPLICATION INSTRUCTIONS

Application conditions

Temperature of air and surface should be up to +5°C, relative humidity of the air max. 80%. Cleaning of the surface which have bigger temperature (above +40°C) will cause that Tikkurila Everal Thinner 1050 will evaporate too quickly. Avoid breathing of the vapour.

Thinner should be let into the product with small portions, constantly stirring. The amount of thinner intend for thinning will depend on adhesive of the product and the way of application: according to recommendation for each product; often it is recommend to put max. 5% of thinner.

Environmental protection and waste disposal

Empty cans as well as cans with liquid waste should be taken to a disposal according to the local regulations. For more information please contact local authority.

Health and Safety

Contains: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics. **Danger.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. Store locked up. Repeated exposure may cause skin dryness or cracking.



GHS02



GHS07



GHS08

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.