



TIKKURILA

FEELINGS UNIVERSAL PRIMER

LOW-ODOUR ACRYLATE PRIMER

DESCRIPTION

Matt-finish low-odour waterborne acrylate latex primer for use on interior walls and ceilings. Offers a first-class foundation for subsequent coats of Feelings Extra Durable coating, Feelings Interior Paint and Feelings Ceiling Paint.

RECOMMENDED USES

For priming of plaster, concrete, filler treated, gypsum, chipboard and wood fibre board surfaces. Suitable for new surfaces and for maintenance painting of previously painted surfaces. Feelings Universal Primer is a good choice under wallpapers. In wallpapering please note that the filler substrate must be made with a suitable Presto ready-to-use filler or cement reinforced dry filler, which does not easily dissolve in water. It has a good adhesion on galvanized surfaces.

PRODUCT FEATURES

Interior walls and ceilings, especially when good adhesion is required, like wall surfaces to be wallpapered.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

FEELINGS UNIVERSAL PRIMER

TECHNICAL DATA	
Base paints	AP BASE
Colour Shades	<p>Color cards: Symphony Color System. Light shades can be tinted in Tikkurila colors. Color accuracy can differ from the sample.</p>
Gloss	Full matt.
Coverage	<p>Theoretical coverage 8-10 m²/l. Practical coverage depends on the application method, conditions, shape and roughness of the surface to be treated.</p>
Can sizes	2.7 l, 9 l
Application method	<p>Roller or spray.</p> <p>For airless spray application, use a nozzle 0.015" - 0.021" or 0,380 - 0,530 mm, thinning 0-5 % by volume</p>
Drying time	Dust dry after 1/2 hour. Re-coatable after 2-4 hours. Wallpaper can be hung the following day.
Density (kg/l)	approx. 1.4 kg/l, (ISO 2811)
Chemical resistance	Resists cleaning detergents and weak solvents, e.g. White Spirit.
Wet scrub resistance	SFS-EN 13300 class II, ISO 11998.
Heat resistance	85°C, (ISO 4211-3)
Volume solids (%)	35
VOC	(cat A/g) 30g/l (2010)
Storage	Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



FEELINGS UNIVERSAL PRIMER

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the temperature of the air at least +5°C, and the relative humidity of the air below 80 %.

Surface preparation

New surfaces:

Remove dirt and dust. Fill the surfaces with a suitable Presto filler, if needed, and sand the dried surface. Remove sanding dust.

Previously painted surfaces:

Wash down previously painted surfaces with Maalipesu cleaning detergent and rinse carefully with water. Fill cracks and holes with a suitable Presto filler and sand the dried surface. Remove sanding dust.

Application

Stir Feelings Universal Primer well before use and thin with water, if necessary. Apply 1-2 times by roller or spray. Finishing paint can be acrylate paint like Feelings Interior Paint, Lumi Interior Paint, Joker or Remontti-Ässä.

Cleaning of tools

Clean tools immediately after use with water.

Maintenance instructions

At the earliest after approx. 1 month from finishing. The surfaces are cleaned with a well squeezed damp sponge or cleaning cloth and neutral (pH 6 – 8) washing detergent. Dilution instructions given by the detergent producer have to be followed by preparing the washing dilution. The surface must be dried after the cleaning.

The product achieves its final hardness and durability after one month under normal conditions, therefore the surfaces must be handled with care during this time. If the surfaces need to be cleaned soon after finishing, clean them lightly with a damp cleaning cloth.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Wear protective gloves. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.