



TIKKURILA  
**HOMEENPOISTO**  
NEW QUALITY!

**DESCRIPTION** Mold removal for wooden and masonry surfaces.

**RECOMMENDED USES** Untreated and painted moldy exterior surfaces.

**PRODUCT FEATURES** For removing mold and algae from painted and unpainted wood, rendered and concrete surfaces before new- or maintenance painting, and from concrete tile and fiber cement surfaces before maintenance painting. No maintenance painting is needed after using Homeenpoisto on already painted surfaces if the surfaces are in good condition.



# HOMEENPOISTO

## TECHNICAL DATA

<b>Coverage</b>	Depends on the cleaning requirement.
<b>Can sizes</b>	1 l, 5 l
<b>Thinner</b>	Water
<b>pH value</b>	Dilute solution approx. 12.
<b>Application method</b>	Spray, sponge or brush.
<b>Density (kg/l)</b>	Approx. 1.1 kg/l, ISO 2811
<b>Storage</b>	Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# HOMEENPOISTO

## APPLICATION INSTRUCTIONS

### Mixing components

Dilute Mould Removal with water, mixing ratio 1:3.

### Surface preparation

Protect glass, aluminum and other similar surfaces that could be damaged by the detergent.

### Application

Dilute Tikkurila Homeenpoisto with water to a ratio of 1:3. Apply the diluted mixture on the moldy facade from the bottom up with a sponge, soft brush or, for large areas, a garden hose. Cleaning from the top down can leave streaks on the facade. Let the solution act for about 30 minutes. You can leave the solution on for longer if the substrate is very moldy. Use a brush if necessary. After the treatment, rinse the surfaces carefully with clean water from the top down, e.g. with a hose.

### Cleaning of tools

Clean tools with water.

### Environmental protection and waste disposal

Recycle empty, dry cans or dispose them of in accordance with local regulations. Do not empty undiluted solution into drains, water systems and soil. Destroy the undiluted liquid waste according to the local regulations for hazardous waste.

### Health and Safety

**Contains:** alkyl(C12-16)dimethylbenzylammonium chloride. **Danger.** Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/clothing and eye/face protection. Contains < 5%: BENZALKONIUM CHLORIDE, cationic surfactants, < 5 % non-ionic surfactants. List of ingredients: Aqua, PEG-5-Laureth-5, benzalkonium chloride, tetrasodium glutamate diacetate, sodium metasilicate 5-hydrate (<https://ec.europa.eu/growth/tools-databases/cosing/>).



GHS05

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.