



TIKKURILA

HOMEENPOISTOTABLETTI

MOULD REMOVAL DETERGENT TABLETS

**DESCRIPTION**

Water-soluble tablets.

RECOMMENDED USES

Untreated and painted moldy exterior surfaces.

PRODUCT FEATURES

For removing mold from painted and unpainted wood, rendered and concrete surfaces before new or maintenance painting, and from concrete tile and fiber cement roofs before maintenance painting.



HOMEENPOISTOTABLETTI

TECHNICAL DATA

Coverage	Depends on the cleaning requirement.
Application method	Spray, sponge or brush.
Density (kg/l)	Average weight 17.36 g/tablet.
Storage	Unaffected by cold storage or transportation.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



HOMEENPOISTOTABLETTI

APPLICATION INSTRUCTIONS

Mixing components

Dissolve one or two tablets into one liter of water, depending on how dirty the surface is.

Surface preparation

Protect glass, aluminum and other similar surfaces that could be damaged by the detergent. Take care not to splash the product on clothes and, for example, untreated furniture. The product has a bleaching effect.

Application

Spread the solution onto the moldy facade from the bottom up, using a garden hose or watering can. Cleaning from the top down can leave streaks on the facade. Let the solution take effect for 15 minutes if necessary, but do not let the surface dry. You can improve the cleaning result by scrubbing with a brush. After the treatment, rinse the surfaces carefully with clean water from the top down, e.g. with a spray gun.

Use only the number of tablets that you will need for a single application. Do not keep the left-over solution.

Before applying the finish, prime unpainted wood surfaces with Valtti-Pohjuste or Valtti Plus Base immediately when dry. Apply a maintenance coat to previously painted surfaces.

Aftercare

Prime the unpainted wood surface as soon as the surface is dry with Valtti Pohjuste or Valtti Akvabase priming oil before finishing treatment. Carry out maintenance painting of previously painted surface.

Cleaning of tools

Clean tools with water.

Environmental protection and waste disposal

Recycle empty, dry cans or dispose them of in accordance with local regulations. Do not empty undiluted solution into drains, water systems and soil. Destroy the undiluted liquid waste according to the local regulations for hazardous waste.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.