



TIKKURILA  
**ISO A-CLEAN**

<b>DESCRIPTION</b>	Water-dilutable cleaning product
<b>RECOMMENDED USES</b>	Iso A-Clean is to be used on outside surfaces, such as roofs, facades, paving stones, skylight windows, plinth courses and walls.
<b>PRODUCT FEATURES</b>	Removes dirt and grease effectively.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



TIKKURILA

## ISO A-CLEAN

### TECHNICAL DATA

<b>Gloss</b>	-
<b>Coverage</b>	2 -6 m <sup>2</sup> /l The practical spreading rate depends on application method, form and surface of the material.
<b>Can sizes</b>	5 l, 25 l, 200 l, 950 l
<b>Mixing ratio</b>	To be diluted to 1-2%
<b>Application method</b>	<p>Use protective gloves and safety glasses during application. Iso A-Clean is supplied as a concentrate</p> <ul style="list-style-type: none"><li>- Ready-to-use solution for very dirty surfaces: 1 part of Iso A-Clean to 25 parts of water (2 % solution)</li><li>- Ready-to-use solution for ordinary maintenance and cleaning before painting: 1 part of Iso A-Clean to 50 parts of water (1 % solution)</li></ul> <p>Apply with paintbrush, brush or sprayer (high/low pressure) When cleaning vertical surfaces, it is recommended to use a low-pressure sprayer in addition to paintbrush and brush Only apply Iso A-Clean until the surface is saturated.</p> <p>All excess liquid must be collected. Do not channel into the ground, streams, or drains. Always make a test coat to ensure the compatibility of product and surface. The use of a higher concentration will not increase the effectiveness of Iso A-Clean.</p>
<b>Drying time</b>	-
<b>Density (kg/l)</b>	1
<b>Volume solids (%)</b>	50
<b>VOC</b>	<p>Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations. Recycle or dispose of empty, dry cans in accordance with local regulations</p> <p>VOC: Max. 30 g/l (Kat. A/h)</p>



# ISO A-CLEAN

## APPLICATION INSTRUCTIONS

### Application conditions

The temperature must be between 5° C and 30° C.

### Priming

Clean using high-pressure. Apply Iso A-Clean in ready-to-use solution when the surface is dry.

If Iso A-Clean is used for ordinary maintenance, a pre-treatment is not necessary.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.