

TIKKURILA

JOKER

DURABLE MATT INTERIOR PAINT

DESCRIPTION

Solvent-free, wash resistant matt paint which creates silky effect surface.

RECOMMENDED USES

For painting ceilings and walls in living rooms, bedrooms and children's rooms as well as entrance halls, kitchens and similar dry premises.

PRODUCT FEATURES

For interior painting. Suitable for plaster, concrete, filler-treated, brick, cardboard, wood surfaces, cardboard-covered plasterboard, chipboard and wood fiberboard. Suitable for both new and previously painted surfaces. Not suitable for painting doors and furniture.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

JOKER

TECHNICAL DATA

Base paints	A BASE, C BASE
Colour Shades	**Color cards:** Feel the Color, Symphony Color System, Deco Grey colour card, Deco Grey Opaques, Feel the Color 2020, Color Now 2023, Tikkurila X Marie Olsson Nylander, Color Now 2025, Color Now 2027, Color Now 2026 Can be tinted in Tikkurila colors.
Gloss	Matt. 5/RT-classification
Coverage	Theoretical coverage: 8- 12 m²/l. Recommended dry film thickness: 32- 47um. Practical coverage depends on the application method, conditions and the shape and the roughness of the surface to be treated.
Can sizes	A BASE: 0.225 l, 0.9 l, 2.7 l, 7.2 l, 9 l, 18 l, 1000 l C BASE: 0.225 l, 0.9 l, 2.7 l, 7.2 l, 9 l, 1000 l FACTORY READYMADE SHADE: 1000 l
Thinner	Water
Application method	Roller, brush or spray. Airless spraying – nozzle 0.015"–0.021" – thinning 0–10% by volume.
Drying time	Dust dry after 30 minutes. Recoatable after 1–2 hours.
Density (kg/l)	Approx. 1.3 kg/l depending on shade, ISO 2811.
Chemical resistance	Resistant to cleaning with mild detergents.
Wet scrub resistance	SFS-EN 13300 class I, ISO 11998.
Heat resistance	85°C, ISO 4211-2 and ISO 4211-3
Volume solids (%)	40
VOC	(cat A/a) max. 30 g/l (2010). Joker contains less than 2 g/l.
Storage	Protect from frost. Badly closed or short cans and/or tinted products do not withstand long storage. Tinted products should be used during the same painting season.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

JOKER

APPLICATION INSTRUCTIONS

Application conditions
The surface to be painted must be dry, the ambient temperature at least +10 °C and the relative humidity of air below 80%.

Surface preparation
Unpainted surfaces:

Clean the new surfaces by removing any dirt and dust. If necessary, level the surfaces with a suitable Presto filler and sand the dried surface. Remove the sanding dust. Prime with Varma primer, for example.

Previously painted surfaces:

Wash surfaces with Seinäpesu detergent. Sand the painted surfaces non-glossy. Remove the sanding dust. Fill any cracks and holes with a suitable Presto filler and sand the dried surface. Remove the sanding dust. If necessary, prime with e.g. Varma primer before applying the top coat.

Painting
Stir Joker well before use and thin with water, if necessary. Apply 1–2 coats by roller, brush or spray.

Cleaning of tools
Remove excess paint/ lacquer from tools and clean with water. Clean the tools with water and soap. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Maintenance instructions
If needed, after approx. 1 month from treating the surface, at the earliest.

Clean the surfaces with a neutral (pH 6–8) cleaning solution and e.g. a sponge or cleaning cloth. Clean very dirty surfaces with a mild alkaline (pH 8–10) cleaning solution and e.g. a cleaning cloth or sponge. After washing, rinse the surface thoroughly. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

After surface treatment, surfaces must be handled with care for a few weeks, as the product will reach its final hardness and durability after about a month under normal conditions. If the surfaces need to be cleaned soon after finishing, clean them lightly with a damp cleaning cloth.

Maintenance treatment
Surfaces painted with Joker can be maintenance painted with same or same kind of waterborne paint. See Preparation.

Environmental protection and waste disposal
Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Minimise paint wastage by estimating how much paint you will need. Reuse of paint can effectively minimise the products' life cycle environmental impact. Recover unused paint for re-use.

Health and Safety
The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Wear protective gloves. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

JOKER

produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: C(M)IT/MIT (3:1) and BIT. If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.