



TIKKURILA

KATTOMUSTA

BACKGROUND PAINT

DESCRIPTION

Black, full-matte ceiling paint.

RECOMMENDED USES

Primarily designed for painting the backs of interior lattice ceilings. Also adheres well to galvanized surfaces.

PRODUCT FEATURES

For painting concrete, rendered, filler and woodfiber board surfaces according to instructions.



KATTOMUSTA

TECHNICAL DATA

Colour Shades	Black.
Gloss	Full matt. 6/RT-classification
Coverage	Filler-treated and woodfiber board surfaces 7–9 m ² /l. Concrete and rendered surfaces 3–5 m ² /l.
Can sizes	10 l, 20 l
Thinner	Water
Application method	Roller, brush or spray application. Airless spray nozzle 0.018–0.023" – thinning 0–10 vol-%.
Drying time	Dust-dry in 30 minutes. Recoatable in 1–2 hours.
Density (kg/l)	1.4 kg/l, ISO 2811.
Heat resistance	85 °C, ISO 4211-3.
Volume solids (%)	33
VOC	(cat A/a) max. 30g/l (2010). Kattomusta contains VOC max. 30g/l.
Storage	Protect from frost.



KATTOMUSTA

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the temperature at least +5°C and the relative humidity of the air below 80%.

Surface preparation

Unpainted surfaces:

Clean new surfaces by removing any dirt and dust. If necessary, level the surfaces with a suitable Tikkurila Presto or Prestonit filler and sand the dried surface.

Previously painted surfaces:

Wash previously painted surfaces with Maalipesu detergent. Sand painted surfaces to a matte finish. Remove the sanding dust. Fill holes and cracks with Presto filler and sand the dried surface. Remove the sanding dust.

Painting

Stir Kattomusta well before use and dilute with water if necessary. Apply one or two coats with a roller, brush or spray gun.

Cleaning of tools

Wash the tools with water. Tikkurila Pensselipesu is recommended for paint that has hardened to a certain extent.

Maintenance instructions

Clean the surfaces with a vacuum cleaner, soft brush or dust towel. Do not use water.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Safety data sheet available on request. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1). Wear protective gloves.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.