


C TYPE-EXAMINATION CERTIFICATE

according to Marine Equipment Directive (Module B)



NOTIFIED BODY 0809

This is to certify that Eurofins Expert Services Ltd did undertake the relevant type approval procedures for the type of equipment identified below which was found to be in compliance with the requirements of Marine Equipment Directive (MED) 2014/90/EU and Commission implementing regulation (EU) 2023/1667 subject to any conditions in the schedule attached hereto.

Intact 8

meet the requirements imposed in IMO 2010 FTP Code, Annex 1 Part 2 and Part 5 (IMO Resolution MSC.307(88) Annex 1 Part 2 and Part 5) on

materials with low flame-spread characteristics and not producing excessive quantities of smoke and toxic products or not giving rise to toxic hazards at elevated temperatures

and the provisions of Marine Equipment Directive 2014/90/EU, that apply to

surface materials with low flame-spread characteristics.

These products have been assigned a U.S. Coast Guard Module B number (**164.112 / EC0809**) to note type approval to Module B only as it pertains to obtaining U.S. Coast Guard approval as allowed by the "Agreement between the European Community and the United States of America on Mutual Recognition of Certificates of Conformity for Marine Equipment" signed February 27th, 2004.

Manufacturer of the product is

Tikkurila Oyj

The Certificate is valid until March 27, 2029 unless suspended, expired or withdrawn, provided the conditions in this certificate are complied with and the equipment remains satisfactory in service.

Espoo March 27, 2024

This document is electronically approved

Katja Vahtikari
Manager, Construction Certification

Heli Välimäki
Senior Expert

Manufacturer	Tikkurila Oyj Heidehofintie 2 FI-01301 Vantaa Finland.
Regulation Item	MED /3.18b, surface materials with low flame-spread characteristics, paint systems.
Product description	Intact 8, Waterborne furniture paint, all colours.
Approved application	On non-combustible, non-metallic substrates with a density of 650 kg/m ³ or higher and a thickness of 25 mm or greater. Dry film thickness (dft) of the paint is max. 62 µm and quantity of dry paint max. 68 g/m ² . On any metallic substrate with a thickness of 0,56 mm or greater. Dry film thickness (dft) of the paint is max. 62 µm and quantity of dry paint max. 63 g/m ² .
Technical document	Intact 8 - Product data sheet 06.09.2022.
Test reports	VTT-S-02617-18, 28.5.2018, VTT Expert Services Ltd., Finland. (on non-metallic, non-combustible substrate) VTT-S-02623-18, 28.5.2018, VTT Expert Services Ltd., Finland. (on metal sheets)
Test methods	IMO 2010 FTP Code Annex 1 Part 2 and Part 5 (IMO Resolution MSC.307(88) Annex 1 Part 2 and Part 5).
Notes	<p>This certificate replaces the previous EC Type-Examination Certificate (B-module) EUFI29-19001771-MED.</p> <p>This certificate will not be valid if the manufacturer makes any changes or modifications to the approved equipment, which have not been notified to, and agreed with the notified body named on this certificate.</p> <p>Should the specified regulations or standards be amended during the validity of this certificate, the product is to be reapproved prior to it being placed on board vessels to which the amended regulations or standards apply.</p> <p>The Mark of Conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-control phase module (D, E or F) of Annex B of the Directive is fully complied with and controlled by a written inspection agreement with a notified body.</p>

END OF CERTIFICATE