



TIKKURILA

PATIO VERSO

WOOD OIL FOR GROWING BOXES / CARBON BLACK, BARN GREY, BARK BROWN, FOREST GREEN

- DESCRIPTION** Water-borne wood oil based on natural oil derivatives. Protects wood against moisture and dirt, and retards splitting and cracking of wood.
- RECOMMENDED USES** Growing boxes, wooden structures of greenhouses.
- PRODUCT FEATURES** Suitable for untreated or previously oil-treated wood.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



PATIO VERSO

TECHNICAL DATA

Colour Shades	Carbon black, Barn grey, Bark brown and Forest green
Coverage	5-7 m ² /l on old and worn wood surface 7-15 m ² /l on new surface and wood surface in good condition
Can sizes	0.33 l, 0.9 l
Application method	Brush or sponge.
Drying time	Touch-dry after a few hours under normal conditions. The porosity of the substrate and the amount of oil used affect the drying time.
Density (kg/l)	1,0 kg/l, ISO 2811.
Volume solids (%)	18

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



PATIO VERSO

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry and the moisture content of the wood must be below 20 %, because wet wood does not absorb oil and oil dries slowly.

During treatment and drying the temperature of the air must be at least +5°C, and the relative humidity of the air below 80%.

Surface preparation

Untreated surfaces:

Clean the wood surface of any dirt, dust and loose material. Wash moldy wood surfaces with Laituripesu according to instructions.

Surface treated previously with wood oil:

Remove loose material with a scraper and/or a wire brush. Clean the surface and, if necessary, wash with Laituripesu according to instructions. If a visible film remains on the surface, remove it before treatment.

Application

Stir Patio Verso thoroughly before use and from time to time during application. Spread the oil tightly with a brush or a sponge so that the oil is absorbed evenly into the wood. Wipe off any excess oil. Spread evenly along the entire length of the board in continuous strokes to avoid overlapping. Apply one coat.

Oil treatment makes the wood look darker.

Carry out maintenance when necessary. Surfaces continuously exposed to the weather may need to be treated annually.

Cleaning of tools

Clean the tools with water and soap Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Maintenance instructions

Handle a new surface with care for approx. one week to allow the product to achieve its final hardness and durability. The surface can be cleaned lightly with a soft brush or mop in approx. two days from the surface treatment, if necessary.

A dirty surface can be cleaned with Laituripesu (mix 1 part of Laituripesu with 10 parts of water).

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

Health and Safety

Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1). Wear protective gloves.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.