



TIKKURILA

PROSEAL

WATER-BORNE PRIMER

DESCRIPTION

ProSeal is a water-borne primer with good penetrating properties. To be used for absorbing surfaces before applying BioRid, BioRid Spray or AsbestGuard.

RECOMMENDED USES

ProSeal is suitable for priming of interior walls and ceilings, on absorbing substrates. ProSeal can also be used for binding asbestos dust. Read the application instructions carefully before painting.

PRODUCT FEATURES

ProSeal is a water-borne primer with good penetrating properties. To be used for absorbing surfaces before applying BioRid, BioRid Spray or AsbestGuard.

PROSEAL

TECHNICAL DATA

| | |
|---------------------------|--|
| Gloss | Full matt. Not applicable. |
| Coverage | Depending on the porosity of the substrate, 2-10 m ² /l . |
| Can sizes | 5 l, 25 l |
| Thinner | Water |
| Application method | Brush, roller, or spray. |
| Drying time | Dry to touch after 1-2 hours. Leave to dry 2-3 hours before repainting. |
| Density (kg/l) | approx. 1.2 kg/l (ISO 2811) |
| Volume solids (%) | 13 |
| VOC | (cat A/h) 50g/l (2010) ProSeal contains VOC max. 50g/l. |
| Storage | Must be protected from frost. Store in a dry and cool place, protected from sunlight. Close the can carefully for the next use. The opened container does not withstand long-term storage. |



PROSEAL

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the temperature at least +5°C and the relative humidity of the air below 80%.

Surface preparation

Remove dirt and dust from the surfaces. Apply BioWash on mold affected surfaces according to instructions. Let the surface dry. Fill the surfaces with suitable Presto or Prestonit filler, if needed. Remove the sanding dust.

Priming

Apply ProSeal 1 time with brush, roller or spray. ProSeal should not be diluted.

Painting

Spread once with roller, spray or brush. The product is used without thinning.

Cleaning of tools

Remove excess paint from tools and wash with water. Tikkurila Pensselipesu is recommended for products that have hardened to a certain extent.

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Harmful to aquatic life with long lasting effects. Avoid release to the environment. Wear protective gloves. Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)) and 2-octyl-2H-isothiazol-3-one (OIT). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.