



TIKKURILA

# REMONTTI-ÄSSÄ

EXTRA DURABLE, SEMI- MATT RENOVATION PAINT.

## DESCRIPTION

Solvent-free, wash- resistant, semi- matt renovation paint for interior use.

## RECOMMENDED USES

For walls and ceilings especially in spaces that require frequent washing, such as kitchens, entrance halls and stairwells. Not suitable for painting furniture.

## PRODUCT FEATURES

Suitable for the interior painting of concrete, plaster, brick, filler-treated, chipboard, cardboard-covered plasterboard and wood fiberboard surfaces. Suitable for both new and previously painted surfaces.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# REMONTTI-ÄSSÄ

## TECHNICAL DATA

<b>Base paints</b>	A BASE, C BASE
<b>Colour Shades</b>	<b>Color cards:</b> Feel the Color, Symphony Color System, Deco Grey colour card, Deco Grey Opaques, Feel the Color 2020, Color Now 2022, Color Now 2023, Tikkurila X Marie Olsson Nylander Can be tinted in Tikkurila colors.
<b>Gloss</b>	Semi-matt. 4/RT - classification
<b>Coverage</b>	Non-absorbent surfaces: 10–12 m <sup>2</sup> /l. Absorbent surfaces: 8–9 m <sup>2</sup> /l.
<b>Can sizes</b>	A BASE: 0.9 l, 2.7 l, 3.6 l, 7.2 l, 9 l, 18 l C BASE: 0.9 l, 2.7 l, 3.6 l, 7.2 l, 9 l
<b>Thinner</b>	Water
<b>Application method</b>	Roller, brush or spray. Airless spraying – nozzle 0.015"–0.021" – thinning 0–5% by volume.
<b>Drying time</b>	Dust dry after 30 minutes. Recoatable after 2 hours.
<b>Density (kg/l)</b>	Approx. 1.3 kg/l depending on shade, ISO 2811.
<b>Chemical resistance</b>	Resistant to cleaning chemicals and mild solvents, such as white spirit.
<b>Wet scrub resistance</b>	SFS-EN 13300 class I, ISO 11998.
<b>Heat resistance</b>	+85 °C, ISO 4211-2 and ISO 4211-3.
<b>Volume solids (%)</b>	40
<b>VOC</b>	(cat A/a) 30g/l(2010). Product contains less than 2 g/l VOC.
<b>Storage</b>	Protect from frost and direct sunlight. Close can carefully for next use. Badly closed or short cans and/or tinted products do not withstand long storage. Tinted products should be used during the same painting season. Protect from frost



# REMONTTI-ÄSSÄ

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry, the ambient temperature at least +10 °C and the relative humidity of air below 80%.

### Surface preparation

Unpainted surfaces:

Clean the new surfaces by removing any dirt and dust. If necessary, level the surfaces with a suitable Presto filler. Remove the sanding dust. Prime with Varma primer.

Previously painted surfaces:

Wash previously painted surfaces with Seinäpesu detergent. Fill any cracks and holes with a suitable Presto filler and sand the dried surface. Sand the painted surfaces non-glossy. Remove the sanding dust. Prime with Varma primer, if necessary.

### Painting

Stir Remontti-Ässä well before use and thin with water, if necessary. Apply 1–2 coats by roller, brush or spray.

### Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

### Maintenance instructions

If needed, after approx. 1 month from treating the surface, at the earliest.

Clean the surfaces with a neutral (pH 6–8) cleaning solution and e.g. a sponge or cleaning cloth. Clean very dirty surfaces with a mild alkaline (pH 8–10) cleaning solution and e.g. a cleaning cloth or sponge. After washing, rinse the surface thoroughly. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

After surface treatment, surfaces must be handled with care for a few weeks, as the product will reach its final hardness and durability after about a month under normal conditions.

If the surfaces need to be cleaned soon after finishing, clean them lightly with a damp cleaning cloth.

### Maintenance treatment

Surfaces painted with Remontti-Ässä can be maintenance painted with same or similar waterborne paint.

### Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

### Health and Safety

The product is not classified as dangerous. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1). Wear protective gloves. Avoid breathing mist/spray. If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.