



TIKKURILA

RUISKUOHENNE 1032

SPRAY THINNER

DESCRIPTION Thinner.

RECOMMENDED USES Thinning

PRODUCT FEATURES For thinning MIRANOL and UNICA alkyd paints for spray application.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



RUISKUOHENNE 1032

TECHNICAL DATA

Can sizes	1 l, 3 l, 10 l
Density (kg/l)	0.72 kg/l, ISO 2811
Storage	Unaffected by cold storage or transportation.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

RUISKUOHENNE 1032

APPLICATION INSTRUCTIONS

Application

An appropriate amount of thinner for thinning MIRANOL and UNICA paints for airless spraying is 5–20 vol-% and 25–35 vol-% for conventional spraying. See the products' directions for use for more information.

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

Contains: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics. **Danger.** Highly flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. Do NOT induce vomiting. Store locked up.



GHS02



GHS08



GHS07



GHS09

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.