



TIKKURILA

INDUSTRY



Temacoat GF-HS Primer

A HIGH-PERFORMANCE ANTI-CORROSIVE
EPOXY PRIMER THAT GIVES AN EVEN FINISH

Hide imperfections for a smoother finish

TEMACOAT GF-HS PRIMER IS AN EASY TO APPLY, HIGH-PERFORMANCE ANTI-CORROSIVE PRIMER



Fast curing with low VOCs

Temacoat GF-HS Primer is a high-performance, two-component anti-corrosive epoxy primer for protecting steel and zinc surfaces, particularly on agricultural and earth-moving machinery. At higher film thicknesses Temacoat GF-HS Primer hides small surface imperfections, meaning putty is not necessarily needed to ensure an even and smooth surface finish. In addition, surfaces coated with Temacoat GF-HS Primer require less sanding, leaving a smooth and dense substrate for the subsequent paint layer and helping to achieve a high-quality final finish.

Because of its high solids content, Temacoat GF-HS Primer has a lower level of volatile organic compounds (VOCs) per litre than traditional epoxies, making it safer for the painter and the environment. Temacoat GF-HS Primer dries and cures quickly even at sub-zero temperatures. This helps to speed up the painting process and increases the efficiency of your operations.

For application instructions please refer to the product data sheet.

BENEFITS

- ☒ FORMS A SMOOTH FINISH THAT HIDES IMPERFECTIONS
- ☒ DRIES FAST FOR A MORE EFFICIENT PAINTING PROCESS
- ☒ LOW VOC CONTENT – BETTER FOR PEOPLE AND THE ENVIRONMENT