



TIKKURILA

INDUSTRY



Temadur HS 90

AN EASY-TO-APPLY POLYURETHANE PAINT
FOR AN OUTSTANDING GLOSSY FINISH

Simply looks good

TEMADUR HS 90 IS
A HIGH-GLOSS,
TWO-COMPONENT
POLYURETHANE PAINT
WITH A HIGH SOLIDS
CONTENT



Easy to apply for an eye- catching finish

Temadur HS 90 is a two-component polyurethane paint with a high solids content. It dries to an extremely smooth and glossy finish similar to that achieved on cars and retains its gloss far longer than conventional polyurethane paints. The painted surface is durable, easy to clean and non-chalking, with good colour retention and excellent weathering and abrasion resistance. Temadur HS 90 is ideal for transport and haulage equipment, storage tank exteriors, steel framework and other steel structures, machinery and equipment. It is particularly recommended for use as a glossy topcoat on epoxy systems exposed to weathering and/or chemical stress.

Because Temadur HS 90 doesn't need to be applied using a wet-on-wet technique it enables a faster throughput time and more efficient production. It can be applied using airless, air-assisted airless or conventional spray and it is easy to achieve a smooth, even surface with standard equipment. Temadur HS 90 has a lower volatile organic compound (VOC) content than conventional polyurethane finishes and has been tested for non-contamination of grain cargo at Newcastle Occupational Health & Hygiene Ltd, UK.

For application instructions please refer to the product data sheet.

BENEFITS

- ☒ FORMS A SMOOTH SURFACE WITH OUTSTANDING GLOSS FINISH
- ☒ EASY TO APPLY FOR A FASTER PAINTING PROCESS
- ☒ DURABLE, EASY TO CLEAN AND NON-CHALKING
- ☒ OFFERS EXCELLENT WEATHER AND ABRASION RESISTANCE