

TIKKURILA

TUNTO HIENO

TEXTURED FINISH / FINE

DESCRIPTION	Water-borne acrylate coating.
RECOMMENDED USES	Walls and ceilings in dry interior spaces.
PRODUCT FEATURES	For new or previously painted concrete, plaster, brick, wooden fiberboard, gypsum board or chipboard surfaces when a textured coating is desired. Tunto Hieno fine texture finish can also be applied to ceilings.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

TUNTO HIENO

TECHNICAL DATA

Base paints	AP BASE, C BASE
Colour Shades	**Color cards:** Tunto Textured Finishes, Symphony Color System, Deco Grey colour card, Feel the Color 2020, Color Now 2022 Can be tinted in Tikkurila colors. Lighting conditions and surface structure of the product will contribute to the final color effect. Product must be premixed before tinting.
Gloss	Full matt.
Coverage	1-9m²/l Varies greatly depending on the painting method - Thick rolling 1-1.5m²/l - Thin rolling 4-5 m²/l - Brushing 2-2.5m²/l - Thick spatula 2-2.5m²/l - Thin spatula 7-9m²/l
Can sizes	AP BASE: 2.7 l, 9 l C BASE: 2.7 l, 9 l
Application method	Apply with roller and for patterning use e.g. a wide brush, wallpaper spatula, firm brush or patterning roller.
Drying time	1-5 hours depending on thickness of the layer.
Density (kg/l)	1.0 kg/l, ISO 2811
Heat resistance	80 °C, ISO 4211-3
Volume solids (%)	53
VOC	(cat A/l) 200g/l(2010). Tunto Hieno contains max 200g/l VOC
Storage	Protect from frost.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

TUNTO HIENO

APPLICATION INSTRUCTIONS

Application conditions
The surface to be treated must be dry, and the temperature of the air, surface and coating must be at least +10 °C and the relative humidity of the air below 80 %.

Surface preparation
Unpainted surfaces:

Remove dirt and dust from the unpainted surfaces. If necessary, smooth the surfaces with a suitable Presto light filler. Prime with Varma primer or Luja Universal . Apply 1–2 coats of Harmony or Nova 7 tinted to the color of the final product.

Previously painted surfaces:

Wash previously painted surfaces with Maalipesu detergent and rinse carefully with water. If necessary, smooth the surfaces with a suitable Presto filler. Use sandpaper to sand glossy painted surfaces until they are matt and remove any sanding dust. If the color difference between the substrate and the finish is significant, apply one coat of Harmony or Nova 7 tinted to the color of the final product.

Painting
Stir Tunto Hieno fine textured finish well before use. Use a roller to apply the product. The surface can be patterned with, for example, a wide brush, wallpaper spatula, firm brush or patterning roller. Spread the coating in a thick layer on interior walls approximately 1 m² at a time and make the final patterning on the surface immediately. Avoid layers that are too thick because they may cause the dry surface to crack. For a homogeneous surface, reserve enough coating mixed in a single container to avoid possible color differences.

Cleaning of tools
Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Maintenance instructions
The surfaces are dry-cleaned by using a vacuum cleaner, soft brush or dust cloth.

Handle the treated surface with care as the product achieves its final hardness and durability in about 1 month under standard conditions.

Maintenance treatment
Leveling a textured surface: If you want a plain paintwork or a different kind of texture, level Tunto surface with suitable Tikkurila Presto filler. Continue treatment from Pretreatment of Unpainted surface.

Environmental protection and waste disposal
Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety
Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains C(M)IT/MIT (3:1). Wear protective gloves.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.