



TIKKURILA

# TUNTO STRUKTUURITAPETTI

- DESCRIPTION** Embossed paintable wallpaper made of polyester cellulose fiber.
- RECOMMENDED USES** Surface material for walls in dry interior spaces.
- PRODUCT FEATURES** A paintable interior substrate for smooth or leveled concrete, plaster, chipboard and wood fiber board surfaces as well as cardboard faced gypsum board surfaces, for repair and new painting sites according to instructions.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



# TUNTO STRUKTUURITAPETTI

## TECHNICAL DATA

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# TUNTO STRUKTUURITAPETTI

## APPLICATION INSTRUCTIONS

### Surface preparation

Remove dirt and dust from the unpainted surfaces. Fill the surfaces with a suitable Tikkurila Presto filler, if needed, and sand the dried surface. Remove sanding dust.

#### Painted surfaces:

Wash previously painted surfaces with Maalipesu cleaning agent and rinse carefully with water. Remove any old flaky and loose paint. Fill any cracks, holes and roughness with a suitable Presto filler. Sand the dried surface. Sand hard and glossy painted surfaces matt and remove the sanding dust.

#### Wallpapered surfaces:

Remove the wallpaper. Fill any cracks and holes with Presto LF renovation filler. Sand and prime the surfaces. Continue treatment following the instructions given above.

### Priming

Apply one coat of primer with Varma primer or Luja Yleispohjamaali universal primer.

Spread an even layer of glue suitable for non-woven wallpaper (e.g. Kiilto Oy's Nowo Seinäliima wall adhesive) onto the dried wall surface, the width of one wallpaper roll at a time.

Attach the Tunto texture wallpaper onto the glued surface tightly, removing any air bubbles, using either a wallpaper brush or a wallpaper trowel. Place the edges, that have been cut ready at the factory, together into a so-called butt joint. By following the alignment the pattern repeats seamlessly. Immediately wipe off any effusive glue with a moist sponge or clean cloth. Trim the ends of the wallpapers with a snap-off knife.

### Painting


The finishing coat can be applied as soon as Tunto texture wallpaper has completely dried onto the surface, in approximately 12 hours at the earliest, depending on the conditions. Paint 1-2 coats with, for example, Harmony or another Tikkurila water-borne interior wall paint according to instructions. Paint coverage approx. 5 m<sup>2</sup>/l.

Tunto texture wallpaper is also suitable for treatment with transparent products, such as Harmony effect finish or Taika pearl glaze. This leaves the embossing visible as slightly lighter than the background. Glazes can be spread with a roller and immediately crisscrossed with a brush. Note that the substrate must be a uniform-color because the wallpaper is semi-transparent.

Note! Wallpaper fixed with Nowo Seinäliima wall adhesive can later be removed with Kiilto Oy's Tapetinpoistoaine wallpaper remover.

# TUNTO STRUKTUURITAPETTI

EN 15102:2007+A1:2011

	
Tikkurila Oyj Kuninkaalantie 1 FI-01300 Vantaa	
13	
TIK-1690-5004	
EN 15102:2007+A1:2011	
Decorative wall covering.	
Release of formaldehyde	Approved
Thermal resistance	NPD
Reaction to fire	D-s3,d2 (CWFT)
Release of other dangerous substances:	
- of heavy metals and specific elements	Approved
- of vinyl chloride monomer (VCM)	Approved
Sound absorption	NPD

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.