



TIKKURILA
TYÖTASOÖLJY
TABLETOP OIL

- DESCRIPTION** A natural oil containing both carnauba and candellilla wax for indoor use.
- RECOMMENDED USES** Solid wood kitchen or bathroom countertops and other indoor wood table tops.
- PRODUCT FEATURES** A finish for bare wood surfaces that is absorbed into wood and provides dirt-, stain-, and water-repellent protection.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

TYÖTASOÖLJY

TECHNICAL DATA

Colour Shades	Colorless, deepens the color of the treated wood.
Gloss	Cannot be specified, depends on the porosity of the surface.
Coverage	9–13 m ² /l, depending on the type of wood. 375 ml is enough for a single treatment of around 3–5 m ² .
Can sizes	0.375 l
Thinner	Water
Application method	Apply with a non-piling cloth.
Drying time (23°C and 50% relative air humidity)	Can be retreated in approx. 24 hours. Dry enough to use in approx. 24 hours.
Volume solids (%)	Approx. 32 p-% of weight.
Storage	Protect from frost.



TYÖTASOÖLJY

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry. The minimum ambient temperature for use of the product is +10 °C and the relative humidity of air below 80%.

Surface preparation

Clean the wood surfaces carefully and let them dry. Washing-up liquid can be used to clean the surfaces. Very dirty or discolored surfaces can be scraped or sanded before treatment.

Application

Apply Työtasoöljy with a clean cloth. If necessary, repeat the treatment after 24 hours.
Treat all visible surfaces of countertops in humid spaces, including undersurfaces.

Cleaning of tools

Clean the tools with Tikkurila Pensselipesu.

Maintenance instructions

Wipe the surface lightly with a damp sponge or cloth and neutral (pH 6–8) washing-up liquid. Do not leave the surface wet. If necessary, apply a new coat of tabletop oil. Very dirty or discolored surfaces can be scraped or sanded before treatment.

Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

Health and Safety

Contains 1,2-benzisothiazol-3(2H)-one (BIT). May produce an allergic reaction. Wear protective gloves.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.