



TIKKURILA

# VALTTI PLUS POHJUSTE

## DESCRIPTION

A clear priming oil used to protect wooden surfaces outdoors. Penetrates easily into the wood fibres, providing very good protection against water absorption even on joints and end wood. Reduces the risk of cracking of wood and paint layers. High durability with Tikkurila exterior wood stain or paint.

## RECOMMENDED USES

All wooden structures to be treated with wood stains or paints (except surfaces to be treated with wood oils and barn-red paints). Woodwork outside. Can be used on wood components above grounds. Not for use on wood in direct soil or water contact. Should always be used together with a wood stain or a paint.

## PRODUCT FEATURES

Suitable for sawn and planed timber, logs, thermally treated and impregnated wood before surface treatment in exterior use.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

## VALTTI PLUS POHJUSTE

### TECHNICAL DATA

<b>Coverage</b>	Sawn wood: 6-8 m <sup>2</sup> /litre per coat. Smooth wood: 8-12 m <sup>2</sup> /litre per coat.
<b>Can sizes</b>	0.9 l, 2.7 l, 9 l
<b>Thinner</b>	No thinning
<b>Application method</b>	Brush or spray. Apply thin coats and quantity that is easily absorbed into the wood. The priming oil dries quickly. Proceed quickly by brush and don't work too long on one point.
<b>Drying time</b>	Touch-dry after approx. 1/2 hour. Finishing coat can be applied after 24 hours.
<b>Density (kg/l)</b>	1.0 kg/l, ISO 2811.
<b>Volume solids (%)</b>	6
<b>Storage</b>	Protect from frost. Badly closed or short cans endure badly long-time storage.



# VALTTI PLUS POHJUSTE

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry. The temperature of the air must be at least +5 °C during treatment and drying, and the relative humidity of the air below 80 %. Do not use the product in the rain or if rain is expected in the next 24 hours.

### Surface preparation

Remove dirt, mold and any loose material from the surface to be treated. Wash down surfaces affected by dirt and mold with Tikkurila Mould Removal (Homeenpoisto) according to directions of use.

Protect other surfaces and plants from splashes of primer. Cover all water containers prior to treatment.

### Application

Treat wood surfaces with Valtti Plus Pohjuste in as early construction phase as possible. Apply the priming oil by brush or spray. Stir before use. Handle the product in a well-ventilated place.

Treat the end surfaces of the wood with special care.

Apply the final surface treatment, for example by painting, as soon as possible, however after 24 hours at the earliest. If the surface treatment is anyhow delayed, prime the surfaces again. The finished surface has to be kept in good condition.

### Cleaning of tools

Clean the tools with water and soap Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

### Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

### Health and Safety

Harmful to aquatic life with long lasting effects. Avoid release to the environment. Wear protective gloves. Contains 3-iodo-2-propynyl butylcarbamate (IPBC). May produce an allergic reaction.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.