



TIKKURILA

VALTTI PRIMER

EXTERIOR WOOD PRIMING OIL

DESCRIPTION

Colorless priming oil for exterior wood

RECOMMENDED USES

For exterior priming of sawn and planed timber, woodwork, logs and impregnated wood before surface treatment.

PRODUCT FEATURES

A clear oil which is used for protecting of joints, end wood and other exposed parts on wood outdoors. Penetrates easily into the wood, which provides good protection against water absorption and reduced risk of cracking in wood and paint layers. Good durability with Tikkurila exterior wood stain or paint



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

VALTTI PRIMER

TECHNICAL DATA

Colour Shades	Colorless.
Gloss	NA
Coverage	Planed surfaces: 8-10 m ² /l; Sawn wood surfaces: 4-5 m ² /l.
Can sizes	0.9 l, 2.7 l, 9 l
Application method	Brush, spray or dip.
Drying time	Touch-dry after approx. 30 min. Recoatable after 24 hours. Attention! In case of low temperatures and high air relative humidity, the drying time may be increased.
Density (kg/l)	about 0,8 kg/l.
Volume solids (%)	15%.
Storage	In tightly closed package, protecting from moisture, heat and direct sunlight. Can withstand storage at low temperatures. In case of storage at subzero temperatures before use the paint should be hold at (+20±2)°C for 24 hours and carefully stirred. Shelf life - 60 months from the production date in unopened original packaging.

VALTTI PRIMER

APPLICATION INSTRUCTIONS

Application conditions

The treated surface should be dry and clean. During application and drying of the product, the temperature must be above +5°C and relative air humidity should be lower than 80%.

Attention! In case of low temperatures and high air relative humidity, the drying time may be increased.

Surface preparation

Clean the surface from dirt, dust and other impurities. Wash contaminated and moldy areas with Tikkurila Mould Remover «Homeenpoisto», observing the instructions for use. Protect unpainted surfaces and plants from splashes of primer Tikkurila «Valtti Primer».

Priming

Prime surfaces with Valtti Primer as early as possible during the construction stage. Prime the surfaces once. Treat the end-grain carefully. Apply the finishing coat as soon as possible, though earliest after 24 hrs of priming.

Cleaning of tools

Clean the tools with White Spirit 1050 or Tikkurila Pensselipesu (Tool Cleaner).

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

Health and Safety

Contains: hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 2-octyl-2H-isothiazol-3-one (OIT). **Danger.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from sparks and open flames. - No smoking. Do not breathe vapor. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. Do NOT induce vomiting. **IF ON SKIN:** Wash with plenty of soap and water. This primer contains a biocidal product for the preservation of the surface treatment. Contains: 2-octyl-2H-isothiazol-3-one (OIT) and 3-iodo-2-propynyl butylcarbamate (IPBC).



GHS02



GHS08



GHS07



GHS09

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.