



TIKKURILA

# VINYL MATT

HIGH PERFORMANCE FULL-MATT INTERIOR PAINT

## DESCRIPTION

Full-matt interior paint with excellent coverage

## RECOMMENDED USES

For painting walls and ceilings in living rooms, bedrooms and children's rooms, as well as other similar dry spaces

## PRODUCT FEATURES

Suitable for the interior painting of concrete, plaster, brick, filler-treated and common building board surfaces on walls in living quarters.



The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

## VINYL MATT

### TECHNICAL DATA

<b>Base paints</b>	A BASE, C BASE
<b>Colour Shades</b>	<b>Color cards:</b> Symphony Color System Can be tinted in Tikkurila colors.
<b>Gloss</b>	Full matt.
<b>Coverage</b>	Theoretical coverage 8-10 m <sup>2</sup> /l. Practical coverage depends on the application method, conditions, shape and roughness of the surface to be treated.
<b>Can sizes</b>	A BASE: 2.7 l, 9 l C BASE: 2.7 l, 9 l
<b>Thinner</b>	Water
<b>Application method</b>	Brush, roller or spray.
<b>Drying time</b>	Dust-dry after 1/2 hours, recoatable after 3 hours
<b>Density (kg/l)</b>	Approx. 1.3 kg/l depending on shade, ISO 2811.
<b>Wet scrub resistance</b>	SFS-EN 13300 class II, ISO 11998.
<b>Volume solids (%)</b>	40
<b>VOC</b>	(cat A/a) 30g/l(2010). Vinyl Matt contains less than 30 g/l VOC.
<b>Storage</b>	Protect from frost. Badly closed or short cans and/or tinted products do not withstand long storage. Tinted products should be used during the same painting season.



# VINYL MATT

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry, the ambient temperature at least +10 °C and the relative humidity of air below 80%.

### Surface preparation

Unpainted surfaces:

Clean the new surfaces by removing any dirt and dust. If necessary, level the surfaces with suitable Tikkurila filler and sand the dried surface. Remove the sanding dust. Prime the surface with Tikkurila Optiva Primer, for example.

Previously painted surfaces:

Wash surfaces with detergent (e.g Tikkurila Seinäpesu). Sand the painted surfaces non-glossy. Remove the sanding dust. Fill any cracks and holes with suitable Tikkurila filler and sand the dried surface. Remove the sanding dust. If necessary prime the surface with Tikkurila Optiva Primer.

### Painting

Stir Vinyl Matt well before use and thin with water, if necessary (up to 5% of the paint volume). Apply 1–2 coats by roller, brush or spray.

### Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

### Maintenance instructions

If needed, after approx. 1 month from treating the surface, at the earliest. The surfaces are cleaned with a dry brush or dust towel. Dirty surfaces are cleaned with a damp cleaning tool moistened in a neutral (pH 6-8) washing solution. The surface may not remain wet after cleaning. Follow the dilution instructions given by the detergent manufacturer when mixing the cleaning solution.

The product achieves its final hardness and durability after one month under normal conditions, and therefore the surfaces must be handled with care during this time. If the surfaces need to be cleaned soon after finishing, clean them lightly with a dry or damp cleaning cloth.

### Maintenance treatment

Surfaces painted with Vinyl Matt interior paint can be maintenance painted with the same or similar water-borne paint. See Pretreatment.

### Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

### Health and Safety

The product is not classified as dangerous. Wear protective gloves. Safety data sheet available on request. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)).

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.