



## TIKKURILA PONTTI PUULATTIAMAALI

- DESCRIPTION** A full coverage acrylate paint for wooden floors. Nordic Ecolabel.
- RECOMMENDED USES** Particularly wood and fiberboard flooring. Perfectly suitable also for repainting floor surfaces previously painted with alkyl or epoxy paints or treated with epoxy varnish.
- PRODUCT FEATURES** Wooden floor and stairs.





TIKKURILA

## PONTTI PUULATTIAMAALI

### TECHNICAL DATA

<b>Base paints</b>	A BASE, C BASE
<b>Colour Shades</b>	Can be tinted in Tikkurila colors.
<b>Gloss</b>	Semi-matt.
<b>Coverage</b>	Approx. 8 m <sup>2</sup> /l.
<b>Can sizes</b>	A BASE: 0.9 l, 2.7 l, 9 l C BASE: 0.9 l, 2.7 l, 9 l
<b>Thinner</b>	Water
<b>Application method</b>	Brush or roller for smooth surfaces.
<b>Drying time (23°C and 50% relative air humidity)</b>	Dust dry in approx. 15 min. Recoatable in approx. 2 h. Ready for light mechanical stress the next day. Full hardness and abrasion properties will be obtained in approx. 2 weeks. Low air temperature and high humidity will increase the opening time of the paint. Avoid laying heavy articles and things which prevent drying – such as carpets – on the floor during the first week.
<b>Chemical resistance</b>	Resists grease and e.g. White Spirit. Does not resist strong solvents likee.g. paint thinner.
<b>Volume solids (%)</b>	37
<b>Weight solids (%)</b>	A-base approx. 1,2 kg/l, ISO 2811 C-base approx. 1,1 kg/l, ISO 2811
<b>VOC</b>	(cat A/i)max.140 g/l (2010). Pontti Puulattiamali contains VOC max. 140 g/l.
<b>Storage</b>	Protect from frost. Protect from frost

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



# PONTTI PUULATTIAMAALI

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry, the temperature of the air at least +10°C, and the relative humidity of the air below 80%.

### Surface preparation

Unpainted surfaces:

Remove all dirt, oil, dust and grease.

Previously painted surfaces:

To remove any dirt and possible wax containing washing solution, wash previously painted or lacquered surfaces with Maalipesu cleaning agent diluted with water to a ratio 1:5. Rinse thoroughly with water and allow to dry. Remove old, flaking paint. Sand the surfaces carefully and remove sanding dust.

### Painting

Stir the paint thoroughly before use.

Bare wood surfaces: Apply 1-2 coats of Multistop Isolation Primer on bare wood surfaces. The best insulation result is achieved when the treatment is performed twice. Finish with 1-2 coats of undiluted Pontti Puulattiamali.

Previously painted or lacquered surfaces: Apply Pontti Puulattiamali directly on the surface 1-2 times with a synthetic brush.

NB. Paint will dry quickly, so plan your work beforehand to avoid paint joints. Apply lengthwise to few planks at a time, and make repairs when the paint has dried.

### Cleaning of tools

Clean tools with water or Tikkurila Pensselipesu (Tool Cleaner). Remove excess paint from tools. Clean tools with water. Tikkurila Pensselipesu (Tool Cleaner) is recommended to be used to remove a bit hardened paint.

### Environmental protection and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

### Health and Safety

Contains 1,2-benzisothiazol-3(2H)-one (BIT). May produce an allergic reaction. Wear protective gloves.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.