



TIKKURILA

## PRESTO PAPERISAUMANAUHA

### DESCRIPTION

Paper sealing strip.

### RECOMMENDED USES

Wall and ceiling surfaces in interior spaces.

### PRODUCT FEATURES

For interior jointing of gypsum boards. Can also be used mechanically with Bazooka automatic taping tool.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

# PRESTO PAPERISAUMANAUHA

## TECHNICAL DATA

<b>Coverage</b>	Length of a roll 75 m, width 52 mm.
<b>Application method</b>	Steel trowel or automatic jointing tool

# PRESTO PAPERISAUMANAUHA

## APPLICATION INSTRUCTIONS

### Application conditions

The surface to be painted must be dry, the temperature at least +5°C and the relative humidity of the air below 80%.

### Surface preparation

Remove any dust and loose material, that reduces adhesion, by brushing.

### Application

#### Manually:

Spread Presto J filler with a steel trowel so that it fills the dent formed by the thinned edges. Press sealing strip onto the filler with the steel trowel. Spread any effusive filler on top of the joint tape. If necessary, add more filler on top of the joint tape until the joint is filled.


#### Mechanically:

Fill the machine with Presto J filler. Work on the joint following the instructions provided by the manufacturer of the device.

After the filler has dried, apply 1–2 coats of Presto light filler. After the filler has dried sand the surfaces with sand paper.

# PRESTO PAPERISAUMANAUHA

EN 13963:2005

	
Tikkurila Oyj Kuninkaalantie 1 FI-01300 Vantaa	
13	
TIK-1690-5001	
EN 13963:2005	
Jointing material of gypsum plasterboards - Type 3A. Jointing material of gypsum plasterboards - Type 1A.	
Dimensional stability - width	Pass
Dimensional stability - length	Pass
Tensile strength	Pass

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.