



TIKKURILA

PUUKITTI

WOOD FILLER

DESCRIPTION

Waterborne special putty.

RECOMMENDED USES

Furniture, doors, panel walls and ceilings and other wood surfaces.

PRODUCT FEATURES

For filling holes in interior wooden surfaces. The filler treated hole is suitable to be stained, varnished or painted.

After drying Spakkeli Wood Putty looks like untreated wood surface.



PUUKITTI

TECHNICAL DATA

Can sizes	0.5 l
Application method	Smoothing trowel
Drying time (23°C and 50% relative air humidity)	Thin filling layer can be sanded after approx. 4 hours and deeper filling layer after 24 hours.
Density (kg/l)	1.8 kg/l, ISO 2811
Volume solids (%)	67

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



PUUKITTI

APPLICATION INSTRUCTIONS

Application conditions

The surface to be treated must be dry, the temperature of the air at least 5 °C, and the relative humidity of the air below 80 %.

Surface preparation

Remove dirt, dust and loose material from the surface.

Apply Spakkeli wood putty with a smoothing trowel. Thin with water, if necessary. Fill large holes preferably twice or several times. Sand the surface and remove sanding dust.

Coating

The surface can be stained with e.g. Parketti-Ässä Stain, Akvi Color or Dicco Color stain.

The finishing treatment with a clear or tinted Kiva Furniture Lacquer, Unica Super or Paneeli-Ässä, Parketti-Ässä Floor Lacquer, Merit Acid Catalysed Lacquer or Akvilac FD range of products depending on the surface.

Note

Note the different coloration of the wood surface and putty surface when applying the finishing coat.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.