



TIKKURILA
RUISKUOHENNE 1032
SPRAY THINNER

DESCRIPTION Thinner.

RECOMMENDED USES Thinning

PRODUCT FEATURES For thinning MIRANOL and UNICA alkyd paints for spray application.





RUISKUOHENNE 1032

TECHNICAL DATA

Can sizes	1 l, 3 l, 10 l
Density (kg/l)	0.72 kg/l, ISO 2811
Storage	Unaffected by cold storage or transportation.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.



RUISKUOHENNE 1032

APPLICATION INSTRUCTIONS

Application

An appropriate amount of thinner for thinning MIRANOL and UNICA paints for airless spraying is 5–20 vol-% and 25–35 vol-% for conventional spraying. See the products' directions for use for more information.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.