



TIKKURILA

SOLID EPOXY THINNER EP-H

DESCRIPTION

Thinner.

RECOMMENDED USES

Thinner for Tikkurila's Solid EP-H epoxy paint.

PRODUCT FEATURES

Used for thinning Solid EP-H epoxy paint and to wash painting tools.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.

SOLID EPOXY THINNER EP-H

TECHNICAL DATA

Can sizes	3 l
Density (kg/l)	0,81 kg/l, ISO 2811
Storage	Unaffected by cold storage or transportation. For professional use only.

SOLID EPOXY THINNER EP-H

APPLICATION INSTRUCTIONS

Application

Solid Epoxy Thinner EP-H is used to thin Solid EP-H epoxy paint. The amount of thinner for priming is 10-30%, for painting 5-20%. See detailed work instructions in the product data sheet of Solid EP-H epoxy paint.

Environmental protection and waste disposal

Avoid spillage into drains, water systems and soil. Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

Health and Safety

DANGER. Highly flammable liquid and vapor. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapors/spray. In case of inadequate ventilation wear respiratory protection.



GHS02

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.