



TIKKURILA

TALON HUOLTOPESU

MAINTENANCE CLEANER FOR WOOD AND MINERAL FACADES

DESCRIPTION

Alkaline universal cleaner for regular cleaning of wood and mineral facades. Painting supplies category 01 (RT classification MaalausRYL 2001). Painting supplies categories 012 and 016 (RT classification MaalausRYL 2012).

RECOMMENDED USES Painted wood and mineral facades.

PRODUCT FEATURES Regular treatment with Talon Huoltopesu keeps facades in good condition by preventing micro-organisms that thrive especially on dirty surfaces from adhering and growing.

TALON HUOLTOPESU

TECHNICAL DATA

Can sizes	1 l, 5 l
Density (kg/l)	1.0 kg/l, ISO 2811
Storage	Protect from frost.

TALON HUOLTOPESU

APPLICATION INSTRUCTIONS

Mixing components

1 part of Talon Huoltipesu, 10 parts of water. Removing stains and cleaning extremely dirty surfaces: 1 part of Tikkurilan Huoltipesu, 1 part of water.

Application

Apply the solution of Talon Huoltipesu and water with a sponge, soft brush or by spraying on the dirty surface from the bottom upwards. Using warm water improves the effect. Let the solution work for approximately 15 minutes and rinse the surface thoroughly with clean water, for example with a garden hose. Avoid excessive pressure when rinsing surfaces with a pressure washer. Brush heavily soiled surfaces to clean them.

Cleaning of tools

Clean tools with water.

Environmental protection and waste disposal

Recycle empty, dry cans or dispose them of in accordance with local regulations. Do not empty undiluted solution into drains, water systems and soil. Destroy the undiluted liquid waste according to the local regulations for hazardous waste.

Health and Safety

WARNING. Flammable liquid and vapor. Causes serious eye irritation. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from sparks and open flames. - No smoking. Avoid breathing vapor. Wear protective gloves. In case of inadequate ventilation wear respiratory protection. IF IN EYES: Rinse cautiously with water for several minutes. Contains < 5 % anionic surfactants, 5 - 15 % non-ionic surfactants and < 5 % phosphates.



GHS02



GHS07

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.